

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ 9.1~10.1	
	VOLTAGE		CURRENT		
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△	2	DIS-E-00002570	TS. ITO	TU. TANIGUCHI	20191007
REMARK			APPROVED	KN. ICHIKAWA	20100705
△ THIS PRODUCT SHALL BE MATED WITH DH40-51S OR DH3 * B-51S, IT APPLIES TO DH40-51S OR DH3 * B-51S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. △ Unless otherwise specified, refer to IEC 60512.			CHECKED	KN. ICHIKAWA	20100705
			DESIGNED	TU. TANIGUCHI	20100705
			DRAWN	TU. TANIGUCHI	20100705
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.
HRS	SPECIFICATION SHEET		PART NO.	DH-51-CV2B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0016-1-00	△ 1/1