

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
<b>APPLICABLE STANDARD</b>									
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C			STORAGE TEMPERATURE RANGE	-55 °C TO 85 °C			
	VOLTAGE	—			OPERATING HUMIDITY RANGE	— % TO — %			
	CURRENT	—			APPLICABLE CABLE	—			
<b>SPECIFICATIONS</b>									
<b>ITEM</b>		<b>TEST METHOD</b>			<b>REQUIREMENTS</b>			<b>QT</b>	<b>AT</b>
<b>CONSTRUCTION</b>									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×	×
MARKING		CONFIRMED VISUALLY.						×	×
<b>ENVIRONMENTAL CHARACTERISTICS</b>									
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -40 → 5~35 → 105 → 5~35 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 10 CYCLES.			NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.			NO HEAVY CORROSION.			×	—
<b>REMARKS</b>					<b>DRAWN</b>	<b>DESIGNED</b>	<b>CHECKED</b>	<b>APPROVED</b>	<b>RELEASED</b>
Unless otherwise specified, refer to JIS C 5402.					<i>F. Soniguchi</i> 06.02.06	<i>F. Soniguchi</i> 06.02.06	<i>Y. Enami</i> 06.02.07	<i>H. Miwa</i> 06.02.08	
					Note QT:Qualification Test AT:Assurance Test O:Applicable Test				
<b>HRS HIROSE ELECTRIC CO., LTD.</b>				<b>SPECIFICATION SHEET</b>		<b>PART NO. FI-20-CV(60)</b>			
CODE NO.(OLD) CL		DRAWING NO. ELC4-040857-01			PART NO. CL230-0501-4-60			1	1

TO
Q