

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-10°C ~ 60°C	STORAGE TEMPERATURE RANGE	-10°C ~ 60°C	
	POWER	-	CHARACTERISTIC IMPEDANCE	-	
<b>SPECIFICATIONS</b>					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
<b>CONSTRUCTION</b>					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK			APPROVED	HO. MIWA	06. 12. 11
Unless otherwise specified, refer to JIS C 5402.			CHECKED	SJ. SHIMIZU	06. 12. 11
			DESIGNED	TS. ITO	06. 12. 08
			DRAWN	TS. ITO	06. 12. 08
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-025739-01	
	SPECIFICATION SHEET		PART NO.	TM-4-DC1	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL222-1364-6-00	1/1