




Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE		STORAGE TEMPERATURE RANGE	
	POWER		CHARACTERISTIC IMPEDANCE	
<b>SPECIFICATIONS</b>				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
				
REMARK  Unless otherwise specified, refer to JIS C 5402.		APPROVED	HO.MIWA	06.10.27
		CHECKED	HO.MIWA	06.10.27
		DESIGNED	SJ.SHIMIZU	06.10.27
		DRAWN	SJ.SHIMIZU	06.10.27
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-043523-01	
	SPECIFICATION SHEET	PART NO.	TM-8-DC1	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL222-2261-9-00	 1/1