

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		USB3.0 SPECIFICATION AND MICRO-USB CABLE AND CONNECTORS SPECIFICATION.			
RATING	OPERATING TEMPERATURE RANGE	-30°C TO +85°C	STORAGE TEMPERATURE RANGE	-30°C TO +60°C	
	VOLTAGE	-	OPERATING HUMIDITY RANGE	- % TO - %	
	CURRENT	-	APPLICABLE CABLE	OUTER DIAMETER OF CABLE : φ 4.8	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
	1	DIS-E-003550	TS. SAKAIZAWA	KN. ICHIKAWA	10.12.20
REMARK HIROSE will not guarantee the performance on these specifications In case this product will be mated with the others which is not HIROSE's. Unless otherwise specified, refer to USB3.0 or EIA 364			APPROVED	KN. ICHIKAWA	10.08.30
			CHECKED	KN. ICHIKAWA	10.08.30
			DESIGNED	HN. ANDO	10.08.27
			DRAWN	HN. ANDO	10.08.27
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-127320-00	
	SPECIFICATION SHEET		PART NO.	ZX360-B-SLDA (4.8)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL242-0508-3-00	1/1