

May.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO
□
□
□
□

| COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE | COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE |
|--|-----------------------------|---|------|---------|---------------------------------|------------------------------------|--------------------------------|---------------------------------|----------|
| △ 4 | DIS-E-001408 | M.S | K.I | 07.3.27 | △ | | | | |
| △ | | | | | △ | | | | |
| APPLICABLE STANDARD | | USB2.0 SPECIFICATION AND △ MICRO-USB CABLES AND CONNECTORS SPECIFICATION | | | | | | | |
| RATING | OPERATING TEMPERATURE RANGE | △-30 °C TO +85 °C | | | STORAGE TEMPERATURE RANGE | △-30 °C TO +85 °C | | | |
| | VOLTAGE | - | | | OPERATING HUMIDITY RANGE | - % TO - % | | | |
| | CURRENT | - | | | APPLICABLE CABLE | OUTER DIAMETER OF CABLE: φ 3.4 | | | |
| SPECIFICATIONS | | | | | | | | | |
| ITEM | | TEST METHOD | | | REQUIREMENTS | | | QT | AT |
| CONSTRUCTION | | | | | | | | | |
| GENERAL EXAMINATION | | VISUALLY AND BY MEASURING INSTRUMENT. | | | ACCORDING TO DRAWING. | | | × | × |
| MARKING | | CONFIRMED VISUALLY. | | | | | | × | × |
| | | | | | | | | | |
| REMARKS △ HIROSE will not guarantee the performance on these specifications in case this product will be mated with the others which is not HIROSE's. | | | | | DRAWN M.SHIMOYAMA 07.1.30 | DESIGNED M.SHIMOYAMA 07.1.30 | CHECKED R.KOYAMA 07.1.31 | APPROVED A.SUZUKI 07.1.31 | RELEASED |
| Unless otherwise specified, refer to USB2.0 or EIA364 | | | | | | | | | |
| Note QT:Qualification Test AT:Assurance Test ×:Applicable Test | | | | | | | | | |
| HRS HIROSE ELECTRIC CO., LTD. | | | | | SPECIFICATION SHEET | | | PART NO. ZX64-B-SLDA | |
| CODE NO.(OLD) CL | | DRAWING NO. ELC4-126087 | | | CODE NO. CL242-0013-0 | | | 1/1 | |