


Capacitor, ceramic, 2200 pF, +/-10% Tol, 500V, X7R, Lead Spacing=0.2"



Dimensions (in)

ID	Dimension	Tolerance	Ма
L	0.15	max	Ca
н	0.23	max	Le
т	0.15	max	Vo
S	0.2	+/-0.03	Te
LL	0.276	min	То
F	0.02	+0.004/-0.001	Во
К	0.02		Lea

Specifications

Manufacturer:	KEMET	
Capacitance:	2200 pF	
Lead Spacing:	0.2"	
Voltage:	500V	
Temperature Coefficient:	X7R	
Tolerance:	+/-10%	
Body Type:	Radial Conformal	
Lead Type:	PC-Leads	
Lead Form:	Hockey Stick	
Termination Type:	Tin	
Package Kind:	Bulk	
Package Type:	Bag	
Package Quantity:	500	

Notes:

-Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk



© 2006-2012 IntelliData.net

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.