


Capacitor, ceramic, 470 pF, +/-10% Tol, 100V, X7R, Lead Spacing=0.2"



## **Dimensions (in)**

ID	Dimension	Tolerance
L	0.15	max
н	0.23	max
Т	0.1	max
S	0.2	+/-0.03
LL	0.276	min
F	0.02	+0.004/-0.001
к	0.02	

## **Specifications**

Manufacturer:	KEMET
Capacitance:	470 pF
Lead Spacing:	0.2"
Voltage:	100V
Temperature Coefficient:	X7R
Tolerance:	+/-10%
Body Type:	Radial Conformal
Lead Type:	PC-Leads
Lead Form:	Hockey Stick
Termination Type:	Tin
Package Kind:	T&R
Package Size:	12in
Package Type:	Type 1
Package Quantity:	2500

Notes:

-Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk



© 2006-2012 IntelliData.net

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.