


Capacitor, ceramic, 1600 pF, +/-5% Tol, 500V, C0G, Lead Spacing=0.2"



Specifications

Package Quantity:

500

Dimensions (in)

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	0.2	max	Capacitance:	1600 pF
н	0.26	max	Lead Spacing:	0.2"
т	0.2	max	Voltage:	500V
S	0.2	+/-0.03	Temperature Coefficient:	C0G
LL	0.276	min	Tolerance:	+/-5%
F	0.02	+0.004/-0.001	Body Type:	Radial Conformal
К	0.02		Lead Type:	Standard Leads
G	0.031	ref	Lead Form:	Hockey Stick
			Termination Type:	Tin
			Package Kind:	Bulk
			Package Type:	Bag

Notes:

-Dimension G represents meniscus-free zone above seating plane

-Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk



Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.