


Capacitor, ceramic, 0.1 uF, +/-20% Tol, 50V, Z5U, Lead Spacing=0.2"



Dimensions (in)

ID	Dimension	Tolerance	Manufacture
L	0.2	max	Capacitance
н	0.325	max	Lead Spacir
т	0.125	max	Voltage:
S	0.2	+/-0.03	Temperatur
LL	0.276	min	Tolerance:
F	0.02	+0.004/-0.001	Body Type:
к	0.02		Lead Type:
			Lead Form:

Specifications

Manufacturer:	KEMET
Capacitance:	0.1 uF
Lead Spacing:	0.2"
Voltage:	50V
Temperature Coefficient:	Z5U
Tolerance:	+/-20%
Body Type:	Radial Conformal (Dipped)
Lead Type:	PC-Leads
Lead Form:	Hockey Stick
Termination Type:	Tin-Lead (SnPb)
Package Kind:	Bulk
Package Type:	Bag
Package Quantity:	500

Notes:

-Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk



© 2006-2012 IntelliData.net

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.