
KEMET Part Number: C333C334M5U5TA

(C333C334M5U5TA)



Capacitor, ceramic, 0.33 uF, +/-20% Tol, 50V, Z5U, Lead Spacing=0.2"



Dimensions (in)		
Symbol	Dimension	Tolerance
L	0.3	max
Н	0.39	max
т	0.15	max
S	0.2	+/-0.03
LL	0.276	min
F	0.02	+0.004/-0.001
К	0.02	
G	0.031	ref

Notes:	
--------	--

-Dimension G represents meniscus-free zone above seating plane

-Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk

General Information				
Manufacturer:	KEMET			

Electrical Specifications		
Capacitance:	0.33 uF	
Lead Spacing:	0.2"	
Voltage:	50V	
Temperature Coefficient:	Z5U	
Tolerance:	+/-20%	
Application:	Commercial Standard	
Body Type:	Radial Conformal (Dipped)	
Lead Type:	Standard Leads	
Lead Form:	Crimped In	
Termination Type:	Tin	

Packaging Specifications		
Package Kind:	Bulk	
Package Type:	Bag	
Package Quantity:	250	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006-2012 IntelliData.net