


Aluminum Electrolytic, 85C, EDK, 330 uF, 20%, 6.3 V, -40/+85C



Dimensions	
D	8mm +/-0.5mm
L	6.2mm +/-0.3mm
W	0.65mm +/-0.1mm
F	0.3mm MAX
A	8.3mm +/-0.2mm
B	8.3mm +/-0.2mm
C	9.5mm MAX
E	3.4mm +/-0.2mm
P	2.2mm +/-0.2mm

Packaging Specifications	
Packaging:	T&R, 380mm
Packaging Quantity:	1000

General Information	
Dielectric:	Aluminum Electrolytic
Style:	SMD Can
Series:	EDK
Description:	Surface Mount, Aluminum Electrolytic
RoHS:	Yes
Lead:	V-Chip

Specifications	
Capacitance:	330 uF
Capacitance Tolerance:	20%
Voltage DC:	6.3 VDC, 8 VDC (Surge)
Temperature Range:	-40/+85C
Rated Temperature:	85C
Life:	2000 Hrs
Dissipation Factor:	35%
Current:	300 mAmps (120Hz), 408 mAmps (120Hz 50C)
Leakage Current:	21 uA (2min 20C)
Impedance Ratio at -25C:	4
Impedance Ratio at -40C:	8
High Temperature Solder:	Yes