


Capacitor, ceramic, 0.022 uF, +/-20% Tol, 50V, BX, Lead Spacing=0.2"



Dimensions (in)

ID	Dimension	Tolerance	Manufacturer:
w	0.09	+/-0.01	Capacitance:
н	0.19	+/-0.01	Lead Spacing:
L	0.19	+/-0.01	Voltage:
S	0.2	+/-0.03	Temperature C
LL	1.25	min	Tolerance:
F	0.025	+0.004/-0.002	Body Type:
G	0.026	min	Lead Type:
			Lead Form:

Specifications

Manufacturer:	KEMET	
Capacitance:	0.022 uF	
Lead Spacing:	0.2"	
Voltage:	50V	
Temperature Coefficient:	BX	
Tolerance:	+/-20%	
Body Type:	Radial Molded	
Lead Type:	Standard Leads	
Lead Form:	Hockey Stick	
Package Kind:	Bulk	
Package Type:	Bag	
Package Quantity:	100	

Notes:

-Note A: Center line of the leads will be within 0.03 in [0.76 mm] of the center line of the body.

-Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk



Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.