

Tantalum, MnO2 Tantalum, COTS Multi-Anode, T513\_COTS, 15 uF, 10%, 35 V, 7343, SMD, MnO2, Molded, Military Equivalent, MAT COTS, B (0.1%/1000 Hrs), 100 mOhms, 3.1mm



Dimensions	
Footprint	7343
L	7.3mm +/-0.3mm
W	4.3mm +/-0.3mm
H	2.8mm +/-0.3mm
T	0.13mm REF
S	1.3mm +/-0.3mm
F	2.4mm +/-0.1mm
A	3.8mm MIN
B	0.5mm +/-0.15mm
E	3.5mm REF
G	3.5mm REF
P	0.9mm REF
R	1mm REF
X	0.1mm +/-0.1mm

Packaging Specifications	
Weight:	349.43 mg
Packaging:	T&R, 178mm
Packaging Quantity:	500

General Information	
Dielectric:	MnO2 Tantalum
Style:	SMD Chip
Series:	T513_COTS
Description:	SMD, MnO2, Molded, Military Equivalent, MAT COTS
Features:	Multiple Anode, MAT COTS, Low ESR
RoHS:	No
Termination:	Solder Coated
Notes:	In Polarity Stripe, At KEMET's Option, Type May Be Indicated: No Symbol = Standard (Or Low Leakage) MnO2 Tantalum Chip, O = LowESR T494, R = Low ESR T495, F = Fused T496, HT = 150C Rated T498 (or B45196P, B45198P), H = 175C rated T499, M = Multiple Anode

Specifications	
Capacitance:	15 uF
Capacitance Tolerance:	10%
Voltage DC:	35 VDC (85C), 23.45 VDC (125C)
Temperature Range:	-55/+125C
Dissipation Factor:	6%
Failure Rate:	B (0.1%/1000 Hrs)
Resistance:	100 mOhms (100kHz 20C)
Leakage:	5.3 uAmps (20C)
Testing and Reliability:	Standard Testing Only

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.