

Tantalum, Polymer Tantalum, T520, 33 uF, 20%, 6.3 V, 3528, SMD, Polymer, Molded, Low ESR, Non-Combustible, 35 mOhms, Height Max = 2.1mm



Dimensions

| Dimensions | |
|------------|-----------------|
| Footprint | 3528 |
| L | 3.5mm +/-0.2mm |
| W | 2.8mm +/-0.2mm |
| H | 1.9mm +/-0.2mm |
| T | 0.13mm REF |
| S | 0.8mm +/-0.3mm |
| F | 2.2mm +/-0.1mm |
| A | 1.9mm MIN |
| B | 0.4mm +/-0.15mm |
| P | 0.5mm REF |
| R | 1mm REF |
| X | 0.1mm +/-0.1mm |

Packaging Specifications

| | |
|---------------------|------------|
| Weight: | 94.85 mg |
| Packaging: | T&R, 178mm |
| Packaging Quantity: | 2000 |

General Information

| | |
|--------------|------------------------------------------------|
| Dielectric: | Polymer Tantalum |
| Style: | SMD Chip |
| Series: | T520 |
| Description: | SMD, Polymer, Molded, Low ESR, Non-Combustible |
| Features: | Low ESR |
| RoHS: | Yes |
| Termination: | Tin |

Specifications

| | |
|------------------------|----------------------------------------------------------------|
| Capacitance: | 33 uF |
| Capacitance Tolerance: | 20% |
| Voltage DC: | 6.3 VDC (105C) |
| Temperature Range: | -55/+105C |
| Dissipation Factor: | 8% 120Hz 25C |
| Failure Rate: | N/A |
| Resistance: | 35 mOhms (100kHz 25C) |
| Current: | 1900 mAmps (100kHz 45C), 1330 mAmps (85C), 475 mAmps (105C) |
| Leakage Current: | 20.8 uA (5min 25C) |