


Capacitor, tantalum, 150 uF, 3528, +/-20% Tol, 6.3V@85C



Dimensions (mm)

Specifications

ID	Dimension	Tolerance
L	3.5	+/-0.2
W	2.8	+/-0.2
H	1.5	max
F	2.2	+/-0.1
S	0.8	+/-0.3
X	0.05	ref
T	0.13	ref
A	2.1	min
G	1.8	ref
E	2.2	ref

Manufacturer:	KEMET
Capacitance:	150 uF
Voltage DC @ 85C:	6.3V
Voltage DC @ 105C:	6.3V
Tolerance:	+/-20%
Application:	Low ESR
Body Type:	Molded Chip
Temperature Range:	-55/+105C
ESR:	150 mOhm
Footprint:	3528
Termination:	Tin
Leakage Current:	94.5 uA
Dissipation Factor:	8%
Ripple @ 25C:	0.9 A
Ripple @ 85C:	0.63 A
Ripple @ 105C:	0.225 A
Package Kind:	T&R
Package Quantity:	2000

Notes:

-In polarity stripe, at KEMET's option, type may be indicated:
 no symbol = Standard MnO2 tantalum chip, O = LowESR
 T494, R = Low ESR T495, F = Fused T496, HT = 150C
 rated T498 (or B45196P, B45198P), H = 175C rated T499,
 M = Multiple anode construction T530 (and B45396R), KO
 = Organic cathode T520 or T521, KT = High temp organic
 cathode T525, KM = Multiple anode organic cathode T530,
 FD= Organic cathode face down terminals T528.