




Designers' Choice

SOLDERLESS TERMINALS

Solderless Terminals are made of pure electrolytic (ETP) cooper and tin plated. Insulation is color coded vinyl.

RING TONGUE BUTTED SEAM


NON-INSULATED



Hand Crimp Tool
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	FOR STUD SIZE	W	C	L	E	THK	BARREL	
								LENGTH	I.D.
8200	22/18	6	.25	.22	.60	.47	.030	.25	.070
8201		8	.33	.29	.70	.54	.030	.25	.070
8202		10	.33	.29	.70	.54	.030	.25	.070
8203	16/14	6	.25	.22	.60	.47	.030	.25	.090
8204		8	.33	.29	.70	.54	.030	.25	.090
8205		10	.33	.29	.70	.54	.030	.25	.090
8206	12/10	6	.28	.29	.68	.54	.040	.25	.135
8207		8	.38	.29	.73	.54	.040	.25	.135
8208		10	.38	.29	.73	.54	.040	.25	.135

VINYL INSULATED




Hand Crimp Tool
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	FOR STUD SIZE	W	C	L	E	THK	BARREL		MAX. INSUL. DIA.
								LENGTH	I.D.	
8209	22/18 (Red)	6	.25	.22	.80	.67	.030	.25	.070	.145
8210		8	.33	.29	.90	.74	.030	.25	.070	.145
8211		10	.33	.29	.90	.74	.030	.25	.070	.145
8212	16/14 (Blue)	6	.25	.22	.80	.67	.030	.25	.090	.170
8213		8	.33	.29	.90	.74	.030	.25	.090	.170
8214		10	.33	.29	.90	.74	.030	.25	.090	.170
8215	12/10 (Yellow)	6	.28	.29	.98	.84	.040	.25	.135	.250
8216		8	.38	.29	1.03	.84	.040	.25	.135	.250
8217		10	.38	.29	1.03	.84	.040	.25	.135	.250

BLOCK SPADE BUTTED SEAM


NON-INSULATED



Hand Crimp Tool
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	FOR STUD SIZE	W	C	L	E	THK	BARREL	
								LENGTH	I.D.
8218	22/18	6	.30	.25	.65	.50	.030	.25	.070
8219		8	.30	.25	.65	.50	.030	.25	.070
8220		10	.30	.25	.65	.50	.030	.25	.070
8221	16/14	6	.30	.25	.65	.50	.030	.25	.090
8222		8	.30	.25	.65	.50	.030	.25	.090
8223		10	.30	.25	.65	.50	.030	.25	.090
8224	12/10	6	.32	.29	.73	.54	.040	.25	.135
8225		8	.32	.29	.73	.54	.040	.25	.135
8226		10	.32	.29	.73	.54	.040	.25	.135

VINYL INSULATED




Hand Crimp Tool
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	FOR STUD SIZE	W	C	L	E	THK	BARREL		MAX. INSUL. DIA.
								LENGTH	I.D.	
8227	22/18 (Red)	6	.30	.25	.85	.70	.030	.25	.070	.145
8228		8	.30	.25	.85	.70	.030	.25	.070	.145
8229		10	.30	.25	.85	.70	.030	.25	.070	.145
8230	16/14 (Blue)	6	.30	.25	.85	.70	.030	.25	.090	.175
8231		8	.30	.25	.85	.70	.030	.25	.090	.175
8232		10	.30	.25	.85	.70	.030	.25	.090	.175
8233	12/10 (Yellow)	6	.32	.29	1.03	.84	.040	.25	.135	.255
8234		8	.32	.29	1.03	.84	.040	.25	.135	.255
8235		10	.32	.29	1.03	.84	.040	.25	.135	.255

FLANGED BLOCK SPADE BUTTED SEAM


NON-INSULATED



Hand Crimp Tool
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	FOR STUD SIZE	W	C	L	E	THK	BARREL	
								LENGTH	I.D.
8236	22/18	6	.30	.25	.65	.50	.030	.25	.070
8237		8	.30	.25	.65	.50	.030	.25	.070
8238		10	.30	.25	.65	.50	.030	.25	.070
8239	16/14	6	.30	.25	.65	.50	.030	.25	.090
8240		8	.30	.25	.65	.50	.030	.25	.090
8241		10	.30	.25	.65	.50	.030	.25	.090
8242	12/10	6	.32	.29	.73	.54	.040	.25	.135
8243		8	.32	.29	.73	.54	.040	.25	.135
8244		10	.32	.29	.73	.54	.040	.25	.135

VINYL INSULATED



Hand Crimp Tool
CAT. NO. 1345

CAT. NO.	WIRE RANGE (AWG)	FOR STUD SIZE	W	C	L	E	THK	BARREL		MAX. INSUL. DIA.
								LENGTH	I.D.	
8245	22/18 (Red)	6	.30	.25	.85	.70	.030	.25	.070	.145
8246		8	.30	.25	.85	.70	.030	.25	.070	.145
8247		10	.30	.25	.85	.70	.030	.25	.070	.145
8248	16/14 (Blue)	6	.30	.25	.85	.70	.030	.25	.090	.170
8249		8	.30	.25	.85	.70	.030	.25	.090	.170
8250		10	.30	.25	.85	.70	.030	.25	.090	.170
8251	12/10 (Yellow)	6	.32	.29	1.03	.84	.040	.25	.135	.250
8252		8	.32	.29	1.03	.84	.040	.25	.135	.250
8253		10	.32	.29	1.03	.84	.040	.25	.135	.250