

## SHIELDED 9 VOLT BATTERY STRAPS

- Insulates and shields 9 Volt battery snap-on connector contacts
- Assures safe secure use, reduces the potential of short circuits and prevents tampering with battery contacts
- Protects circuits, prevents unwanted electrical discharge due to unintended grounding
- Protects battery contacts from dust, dirt, and physical damage
- Ideal for rugged applications, made of high impact molded plastic with integral wire lead strain relief

Modifications available with different wire lengths.



### SPECIFICATIONS

**Base:** ABS

**Male/Female Contacts:** Brass, Nickel Plate

**Wires (Red & Black):** #26 AWG, Tinned, .187 (4.8) end strip, UL/CSA1007

\*Tolerance on lead length +/- .250 (6.4)



I STYLE		T STYLE	
MOLDED		MOLDED	
CAT. NO.	*LEAD LENGTH	CAT. NO.	CAT. NO.
84-4	4.00 (101.6)	81-4	81-4
84-6	6.00 (152.4)	81-6	81-6
84-8	8.00 (203.2)	81-8	81-8

## PREMIUM 9 VOLT BATTERY STRAPS

- Fully Assembled
  - Rigid Assembly
  - Ideal for rugged applications, made of high impact molded plastic with integral wire lead strain relief
- Rigidly constructed. Nickel plate, male and female contacts. Female contacts are spring temper. Accepts numerous insertions to meet U.L. approved standards. Provides excellent mechanical strength and low contact resistance. Wires have tinned copper conductors, PVC insulation and the ends are stripped for easy connection.

Wires are rated to 176°F (80°C) and 300V and meet UL/CSA #1061/#1007 requirements.

Modifications available with different wire lengths.

### SPECIFICATIONS

**Contacts:** Phosphor Bronze, Nickel Plate

**Wire:** #26 AWG, 7/34

**End Strip:** .250 (6.4) Long, Tinned

**Base:** Polyethylene

\*Tolerance on lead length +/- .250 (6.4)



**Base Size:**  
1.062 (27.0) x .512 (13.0)

I STYLE		T STYLE	
MOLDED		MOLDED	
CAT. NO.	*LEAD LENGTH	CAT. NO.	CAT. NO.
2238	4.00 (101.6)	2241	2241
2239	6.00 (152.4)	2242	2242
2240	8.00 (203.2)	2243	2243



**Base Size:**  
1.00 (25.4) x .512 (13.0)