


Recommended PCB Layout
(Top View)



Materials and Finish

Housing: PA66
UL 94V-0 Rated
Color: Black

Shield: Brass, Nickel Plated
Contact Material:
Phosphor Bronze
Plating:
Nickel Underplating, 6µ" Gold
Plating on Contact Area,
Tin Plated on Solder Area

Electrical Characteristics

Insulation Resistance:
750 Megohms Min.
Contact Resistance:
20 milliohms Max.
Dielectric Withstanding Voltage:
500V AC for 1 Minute

Mechanical Characteristics

Durability Rating:
500 Mating Cycles Min.
Operating Temperature:
-40°C to +85°C

Insertion Loss (dB Typ)	Return Loss				Cross Talk			CMR (dB Min)	OCL (uH Min)
	at 100Ω	(dB Min)			(dB Min)				
1~100MHz	1~10MHz	10~30MHz	30~60MHz	60~80MHz	1~30MHz	30~60MHz	60~100MHz	1~100MHz	100KHz, 100 mV, 8mA DC
-1.0	-20	-16	-12	-10	-40	-35	-30	-35	350


Tolerances
X.X ± 0.35
X.XX ± 0.25
Unless Stated Otherwise

RoHS COMPLIANT

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	05/09/18	New Drawing	G. Serrato	C. Furumasa	G. Serrato	05/09/18
A0.1	05/29/18	Design Change	G. Serrato	D. Shehan		
A0.2	05/31/18	Updated Specs	D. Shehan			
A1	07/13/18	Release Drawing	C. Kelleher	D. Shehan		

G7LX-A88S7-BP-G/Y

8P8C Mag Jack with POE
Green and Yellow LED



UNITS
mm