


Recommended PCB Layout
(Top View)



Boardlocks not shown in this view

Material and Finish

Shell: Steel, nickel plated
 Insulator: PBT thermoplastic with glass-fiber reinforcement, UL94V-0 rated
 Color: Black

Contact Material:
 Socket - Brass

Contact Plating Options:
 Standard: gold flash on mating end, tin on termination end, nickel underplate on entire contact

15 Option: 15u" gold on mating end, tin on termination end, nickel underplate on entire contact

30 Option: 30u" gold on mating end, tin on termination end, nickel underplate on entire contact

Electrical Specifications

Rated Current: 1.5A
 Rated Voltage: 30Vac
 Insulation Resistance: more than 1000 megohms at 500V DC
 Contact Resistance: 13 milliohms max.
 Dielectric Withstanding Voltage: 1000V for 1 minute
 Operating Temperature: -55°C to +75°C

Ordering Information	
Part Number	Contact Area Plating Finish
K86X-CD-62S-BR	Gold Flash (standard)
K86X-CD-62S-BR15	15u" Gold (15 option)
K86X-CD-62S-BR30	30u" Gold (30 option)



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	01/05/06	New Drawing	R. Aguirre	H. MA	R. Aguirre	01/05/06
A2	1/16/08	ECO# 07-052	WILL H.	H. MA		
A3	10/15/10	Correct Dim.	S. Vien	H. MA		
A4	9/23/14	ECO#14-028	H. MA	P. DalCanto		
A5	12/31/17	ECO #17-033	J. Elbanna	C. Furumasu		

K86X-CD-62S-BR

D-Sub, Vertical, RoHS Compliant

62 pin, Boardlocks

