

Material and Finish

Housing: High Temp., Thermoplastics
 Color - Black
 Contacts: Copper Alloy,
 30u" gold plated on entire contact
 Shell: Stainless Steel, Nickel plated

Electrical Specifications


Rated Current: 1.5A Max.
 Rated Voltage: 5V AC (rms Max.)
 Insulation Resistance:
 1000 megohms Min.
 Contact Resistance:
 30 milliohms max.
 Dielectric Withstanding Voltage:
 100V AC
 Operating Temperature:
 -30°C to +85°C



Tolerances
X.X ± 0.35
X.XX ± 0.25
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	12/12/07	Release Drawing	H. MA	N/A	A. Frederick	08/17/07
A2	02/27/12	ECO #12-009	S. Vien	H. MA		
A3	01/16/13	ECO #12-063	S. Vien	P. DalCanto		
A4	04/26/13	ECO #13-019	W. Cook	P. DalCanto		
A5	07/16/18	Update Address & RoHS	C. Kelleher	C. Furumasu		
A6	03/20/19	ECO #19-029	G. Serrato	D. Shehan		

KMMX-BSMT5SB-30TR



UNITS
mm

Micro USB, Type-B, SMT, 30u" Gold

Black Insulator, RoHS Compliant

