

SKINDICHT® SM LOCK NUTS



Metal Lock Nuts for NPT, PG and Metric Threaded Products

SKINDICHT® SM Lock Nuts are required wherever NPT, PG or Metric cable glands must be fastened to a housing, and tapped holes cannot be provided.

NPT Version



PG & Metric Versions



Technical Data:



Materials:

NPT:

Stamped Steel

PG & Metric:

Nickel-Plated Brass

NPT Zinc-Plated Steel Locknuts

Part Number	Thread Type & Size	Wrenching Flats inches	Nut Thickness inches	Standard Pack Size
811092*	NPT- 3/8"	0.945	.138	100
811093	NPT- 1/2"	1.102	.157	100
811094	NPT- 3/4"	1.378	.157	50
811095	NPT- 1"	1.693	.157	50

* Product features a hex design.

SKINDICHT® SM: PG Brass Lock Nuts

Part Number	Thread Type & Size	Wrenching Flats		Nut Thickness		Standard Pack Size
		inches	mm	inches	mm	
52003490	PG-7	0.591	15	.110	2.8	100
52003500	PG-9	0.709	18	.110	2.8	100
52003510	PG-11	0.827	21	.118	3.0	100
52003520	PG-13	0.906	23	.118	3.0	100
52003530	PG-16	1.024	26	.118	3.0	100
52003540	PG-21	1.260	32	.138	3.5	50
52003550	PG-29	1.614	41	.157	4.0	50
52003560	PG-36	2.008	51	.197	5.0	25
52003570	PG-42	2.362	60	.197	5.0	25
52003580	PG-48	2.520	64	.217	5.5	25

SKINDICHT® SM-M: Metric Brass Lock Nuts

Part Number	Thread Type & Size	Wrenching Flats		Nut Thickness		Standard Pack Size
		inches	mm	inches	mm	
52103000	M-12X1.5	0.591	15	0.118	3.0	100
52103010	M-16X1.5	0.748	19	0.118	3.0	100
52103020	M-20X1.5	0.945	24	0.138	3.5	100
52103030	M-25X1.5	1.181	30	0.157	4.0	100
52103040	M-32X1.5	1.417	36	0.157	4.0	100
52103050	M-40X1.5	1.811	46	0.197	5.0	50
52103060	M-50X1.5	2.362	60	0.197	5.0	50
52103070	M-63X1.5	2.756	70	0.197	5.0	25
52103071	M-75X1.5	2.953	75	0.315	8.0	5
52103072	M-90X2.0	4.016	102	0.394	10.0	1
52103073	M-110X2.0	4.882	124	0.472	12.0	1