


## SKINTOP® SLM/SLRM Strain Relief with Metric Thread

**Complete the Installation**

 SKINTOP® DIX Bushing page 537

 Plugs page 540



SKINTOP® SLM/SLRM is a durable, liquid-tight, easy-to-assemble strain relief cable gland with metric thread that is universally suited for all types of machinery & equipment, including automation, motion control, process control, and robotics.






### Application Advantage

- The heavy duty SKINTOP® design provides great pullout strength and very reliable strain relief
- Superior integrated locking mechanism includes an internal ratchet for vibration-proof protection
- Multi-trapezoidal thread requires just one twist to tighten
- Generous high-quality neoprene bushing provides a liquid-tight and dust-proof hermetic seal

### Approvals



### Technical Data

 <b>Material:</b>	- Body: Polyamide - Bushing: CR	 <b>Color:</b>	Black (RAL 9005), UV resistant Gray (RAL 7001)
 <b>Locknuts:</b>	Included	 <b>IP Protection:</b>	70 PSI IP69K IP68, 5 bar (Exceeds NEMA 6/6P pressure rating)
 <b>Temperature Range:</b>	- Static: -40°C to +100°C - Dynamic: -20°C to +100°C	- Seal:	

Part Number with Locknut		Part Number without Locknut*		Thread Type & Size	UL Status	øF Clamping Range		SW Wrenching Flats (in)	C Overall Length (in)	D Thread Length (in)	Standard Pack Size
Black	Gray	Black	Gray			(in)	(mm)				
<b>SKINTOP® SLM: Standard</b>											
S2507	S1507	53111200	53111000	M12 x 1.5	Recognized	0.138 - 0.276	3.5 - 7.0	0.591	1.181	0.315	100
S2509	S1509	53111210	53111010	M16 x 1.5**	Recognized	0.177 - 0.394	4.5 - 10.0	0.748	1.339	0.315	100
S2513	S1513	53111220	53111020	M20 x 1.5**	Listed	0.276 - 0.512	7.0 - 13.0	0.984	1.457	0.354	100
S2516	S1516	53111230	53111030	M25 x 1.5**	Listed	0.354 - 0.669	9.0 - 17.0	1.181	1.575	0.394	50
S2521	S1521	53111240	53111040	M32 x 1.5	Listed	0.433 - 0.827	11.0 - 21.0	1.417	1.850	0.394	25
S2529	S1529	53111250	53111050	M40 x 1.5	Listed	0.748 - 1.102	19.0 - 28.0	1.811	2.047	0.394	10
S2536	S1536	53111260	53111060	M50 x 1.5	Listed	1.063 - 1.378	27.0 - 35.0	2.165	2.441	0.472	5
S2542	S1542	53111270	53111070	M63 x 1.5	Listed	1.339 - 1.772	34.0 - 45.0	2.598	2.795	0.472	5
<b>SKINTOP® SLRM: Reducer Bushing</b>											
S2607	S1607	53111300	53111100	M12 x 1.5	Recognized	0.039 - 0.197	1.0 - 5.0	0.591	1.181	0.315	100
S2609	S1609	53111310	53111110	M16 x 1.5**	Recognized	0.079 - 0.276	2.0 - 7.0	0.748	1.339	0.315	100
S2613	S1613	53111320	53111120	M20 x 1.5**	Listed	0.197 - 0.394	5.0 - 10.0	0.984	1.457	0.354	100
S2616	S1616	53111330	53111130	M25 x 1.5**	Listed	0.236 - 0.512	6.0 - 13.0	1.181	1.575	0.394	50
S2621	S1621	53111340	53111140	M32 x 1.5	Listed	0.276 - 0.591	7.0 - 15.0	1.417	1.850	0.394	25
S2629	S1629	53111350	53111150	M40 x 1.5	Listed	0.591 - 0.906	15.0 - 23.0	1.811	2.047	0.394	10
S2636	S1636	53111360	53111160	M50 x 1.5	Listed	0.866 - 1.142	22.0 - 29.0	2.165	2.441	0.472	5
S2642	S1642	53111370	53111170	M63 x 1.5	Listed	1.102 - 1.535	28.0 - 39.0	2.598	2.795	0.472	5

\* The use of a locknut is required per UL if the end-use application consists of inserting the cable gland through a non-threaded hole.

\*\* Metric sizes M16, M20, and M25 also available in an extended thread version. To maintain UL rating, please use a locknut.

Orders of 2000 pieces or more per item will be bulk packaged unless otherwise requested.