

SUMMARY

Wires



Image is for illustrative purpose only

| | |
|------------------|-------------------------|
| Series | 0M |
| Termination type | No contacts / Accessory |
| IP rating | 68 |
| AWG wire size | 0.00 - 0.00 |
| Cable Ø | 0.00 - 0.00 mm |
| Status | active |

Download

[Request a quote](#)

[Catalog](#)

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|--|
| Shell Style/Model | BME*: Blanking cap for fixed receptacle(knurled grip) |
| Keying | |
| Housing Material | Aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass |
| Weight | 3.53 g |

Performance

| |
|---------------|
| Configuration |
| Insulator |
| Rated Current |

Specifications

Contact LEMO for performance details.

Others


| | |
|--------------------|---|
| Temp (min / max): | -20°C / +135°C |
| Humidity (max): | 21 days at 95% |
| Gunfire vibration: | 25 Hz - 2000 Hz, 3 axis (Apache helicopter) |
| Vibration-Sine: | 30 g, 3 axes, 12 hr [10 Hz - 2000 Hz] |
| Vibration-Random: | 37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz] |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Shock Resistance: 300 g [3 ms]
 Lighting strike EIA 364-75: 10K amps - 6 times
 Thermal shock: 5 cycles: -65°C to +150°C
 EMI Shielding EIA 364-66A: >= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)
 Salt Spray Corrosion: max. 48 hr

DRAWINGS

Draws



Dimensions

| | A | C | L | N | P | X |
|-----|------|------|------|------|------|------|
| mm. | 13.1 | 12.7 | 23.4 | 85 | 3.9 | 6 |
| in. | 0.52 | 0.50 | 0.92 | 3.35 | 0.15 | 0.24 |

RECOMMENDED BY LEMO

Tools

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.