

| | | | |
|---|--|---|--|
| <p>0291</p> <p>0291-0-15-XX-16-XX-10-0 Hex press-fit in .067 plated thru hole</p> | <p>0293</p> <p>0293-0-15-XX-16-XX-10-0 Press-fit in .067 mounting hole</p> | <p>0287</p> <p>0287-0-15-XX-16-XX-10-0 Solder mount in .065 min. mounting hole Also available on 8mm wide carrier tape: 3,250 parts per 13" reel. Order as: 0287-0-57-XX-16-XX-10-0</p> | <p>0285</p> <p>0285-0-15-XX-16-XX-10-0 Solder mount in .065 min. mounting hole</p> |
|---|--|---|--|

| | | | |
|--|---|--|--|
| <p>0284</p> <p>0284-0-15-XX-16-XX-10-0 Solder mount in .070 min. mounting hole</p> | <p>8114</p> <p>8114-0-15-XX-16-XX-04-0 Press-fit from underside of pc board into .065 mounting hole</p> | <p>0407</p> <p>0407-0-15-XX-16-XX-04-0 Press-fit in .066 mounting hole</p> | <p>0415</p> <p>0415-0-15-XX-16-XX-10-0 Solder mount in .063 min. mounting hole Also available on 24mm wide carrier tape: 1,500 parts per 13" reel. Order as: 0415-0-57-XX-16-XX-10-0</p> |
|--|---|--|--|

| | | | |
|---|---|--|--|
| <p>0303</p> <p>0303-0-19-XX-16-XX-10-0 Wire Termination Press-fit in .067 mounting hole</p> | <p>0306</p> <p>0306-0-19-XX-16-XX-10-0 Wire Termination #18 gage crimp barrel</p> | <p>0273</p> <p>0273-0-15-XX-16-XX-10-0 Press-fit in .078 mounting hole</p> | <p>7520</p> <p>7520-0-15-XX-16-XX-10-0 Press-fit in .066 mounting hole</p> |
|---|---|--|--|

| | | |
|--|---|---|
| <p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p> | <p>ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <p>01 200µ" TIN/LEAD OVER NICKEL</p> <p>80 200µ" TIN OVER NICKEL ◊</p> <p>15 10µ" GOLD OVER NICKEL ◊</p> <p>CONTACT</p> <p>#16 CONTACT (DATA ON PAGE 221)</p> | <p>SPECIFY CONTACT FINISH:</p> <p>01 200µ" TIN/LEAD OVER NICKEL</p> <p>80 200µ" TIN OVER NICKEL ◊</p> <p>27 30µ" GOLD OVER NICKEL ◊</p> |
|--|---|---|

