



注記 NOTES :
 1. 一般公差 : ±0.4
 GENERAL TOLERANCES: ±0.4

| | | | |
|--|------------|---------|----------------|
| OVERALL TIN 0.88µmin | 39000342 | 2478TL | LOOSE |
| OVERAL COPPER 0.5µmin | 39000286 | 2478T | CHAIN |
| ニッケル下地 2 µmMIN. 金 0.35 µmMIN. | 39-00-0344 | 2478GL | バラ状 LOOSE |
| GOLD 0.35 µmMIN. OVER NICKEL 2 µmMIN. | 39-00-0343 | 2478G | チェーン状 CHAIN |
| メッキ PLATING | EDP NO. | ENG.NO. | 形状 FORM |

MATERIAL
 黄銅 BRASS t=0.254

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

| | | | | |
|--|----------|--------------------------|----------------|--------------|
| DIMENSION UNITS | SCALE | moLEX | | |
| mm | 10:1 | STD KK CRIMP REC | | |
| GENERAL TOLERANCES (UNLESS SPECIFIED) | | PRODUCT CUSTOMER DRAWING | | |
| 4 PLACES | ± 0.2 ± | EC NO: 617983 | DRWN: SS06 | 2019/05/20 |
| 3 PLACES | ± 0.25 ± | CHK'D: ISHWARG | APPR: ISHWARG | 2019/05/27 |
| 2 PLACES | ± 0.3 ± | INITIAL REVISION: | DRWN: HHASEGAW | 1993/04/23 |
| 1 PLACE | ± ± | ANGULAR TOL ± 3.0° | APPR: MFUKUSHI | 1996/01/30 |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | THIRD ANGLE PROJECTION | DRAWING | SERIES |
| | | | A3-SIZE | 2478 |
| DOCUMENT NUMBER | | MATERIAL NUMBER | CUSTOMER | SHEET NUMBER |
| SD-2478X | | SEE CHART | GENERAL MARKET | 1 OF 1 |