

Blocks Pluggable and Fixed Mount





Eurostyle™ ESE PCB Terminal Blocks


Pluggable and Fixed Mount

Fulfill your terminal block design requirements with a new and extensive range of ESE PCB terminal blocks from Molex.

Choose from a variety of Molex ESE (Eurostyle Extension) PCB terminal blocks. This new product line includes pitch sizes from 3.50 to 5.08mm (.138 to .200") and is rated at 300V, from 8.0 to 15.0A. Select from fixed (single-piece) or pluggable (two-piece) terminal blocks from circuit sizes 2 through 24.

All ESE PCB terminal blocks from Molex are RoHS compliant and UL recognized for use in the U.S. and Canada. These blocks are compatible with Molex Beau® and other industry standard terminal blocks.

ESE terminal blocks provide economic benefits and enhance Molex's existing Eurostyle terminal block offering. For additional specifications on Eurostyle ESE Terminal Blocks, visit our website: www.molex.com/product/ESEtermblocks.html.





Features and Benefits

- Fixed or pluggable product styles allow for maximum design flexibility
- Three different wire entry angles on fixed mount terminal blocks allow you to choose the best fit for your application
- Two optional styles of imprinting make identifying, testing and wiring easier in the field
- Surface Mount Compatible headers available in 5.00 and 5.08mm (.197 and .200") withstand reflow soldering temperatures, eliminating the need for a secondary wave soldering process
- Gold plating available on any part offers increased connectivity and durability in low power applications
- Captive screws in all terminal blocks mean that screws will not back out of housing or mounting ends

Applications

- Power Distribution
- Factory and Process Automation
- HVAC
- Security Systems
- Elevators
- Irrigation Systems
- Measurement and Control Systems

ESE PCB TERMINAL BLOCK SPECIFICATIONS

Reference Information

Packaging: Box UL File No.: E48521 Flammability: UL 94 V-0

Electrical

Voltage: 300V

Insulation Resistance: 500 Megohms min. Withstanding Voltage: 4000V DC

Mechanical

Operating Temperature:
Standard Plugs and Headers
-40 to +105°C
Surface Mount Compatible Headers
-40 to +140°C

Physical

Housing:

Standard Plugs and Headers — Polyamide (Nylon) 6/6

Surface Mount Compatible Header — Polyamide (Nylon) 4/6

Housing Color: Black (Green or other colors optional)

Screw: Steel M2, M2.5, M3 Contact Plating: Tin (Gold optional)

Imprinting:

Standard -1,2,3Reverse -3,2,1



molex[®] 5.00 and 5.08mm (.197 and .200") Pitch ESE **Fixed Mount Terminal Blocks**



	Pitch	D	C1	W: D	Circuits	Order No.		
	Pittn	Description	Current	Wire Range	CIrcuits	ESE	Beau®	
		Vertical with Rising Cage Clamp	15.0A	14 to 22 AWG	2 to 24	39543-30XX	39890-01XX	
		Vertical with Pressure Clamp		14 to 24 AWG		39543-00XX	39850-16XX	
The		Vertical with Pressure Clamp, Low Profile	10.0A	14 to 22 AWG		39543-06XX	N/A	
	5.00mm (.197")	Horizontal, Molded to length		16 to 24 AWG		39543-31XX	39890-02XX	
		Horizontal, Modular*			2 or 3	39543-45XX	N/A	
		45° Wire Entry with Pressure Clamp, Molded to Length	TU.UA	14 to 24 AWG	2 to 24	39543-02XX	39850-01XX	
		45° Wire Entry with Pressure Clamp, Modular*			2 or 3	39543-05XX	N/A	
		45° Wire Entry with Rising Cage Clamp		14 to 22 AWG	2 to 24	39543-43XX	N/A	
	5.08mm (.200")	Vertical with Rising Cage Clamp	15.0A	12 to 22 AWG	2 to 24	39544-30XX	39880-01XX	

Replace XX with circuit sizes 02 to 24.

* Modular terminal blocks available in 2 or 3 circuits. Blocks can be stacked together to create larger circuit sizes.



3.50mm (.138") Pitch ESE Pluggable Terminal Blocks



	D:a.l.	Decemination	Cumant	Wine Danne	Circuita	Orde	r No.	
	Pitch	Description	Current	Wire Range	Circuits	ESE	Beau®	
PCB Headers								
		Vertical		N/A	2 to 20	39501-10XX	39353-00XX	
07770	0.50 (100%)	Vertical with Threaded Retention Inserts	- 8.0A			39505-10XX	39354-00XX	
	3.50mm (.138")	Horizontal				39502-10XX	39355-00XX	
		Horizontal with Threaded Retention Inserts				39506-10XX	39356-00XX	
Plugs								
		Vertical, Rear Wire Entry		16 to 24 AWG	2 to 20	39503-20XX	N/A	
		Vertical with Retention Screws, Rear Wire Entry				39507-20XX		
	2 50 / 120"\	Vertical, Front Wire Entry	8.0A			39503-30XX		
	3.50mm (.138")	Vertical with Retention Screws, Front Wire Entry	0.UA		Z 10 ZV	39507-30XX		
		Horizontal				39500-00XX	39351-00XX	
		Horizontal with Retention Screws		16 to 30 AWG		39504-00XX	39352-00XX	

Replace XX with circuit sizes 02 to 20.



molex 3.81mm (.150") Pitch **ESE Pluggable Terminal Blocks**



	Diada	Description	Cumant	Wine Danne	Circuita	Orde	r No.	
	Pitch	Description	Current	Wire Range	Circuits	ESE	Beau®	
PCB Headers								
444		Vertical	- 8.0A	N/A	2 to 20	39511-10XX	39900-05XX	
No Marko Ma	2.01/ 1.50 %	Vertical with Threaded Retention Inserts				39515-10XX	39900-11XX	
	3.81mm (.150")	Horizontal				39512-10XX	39900-07XX	
		Horizontal with Threaded Retention Inserts				39516-10XX	39900-12XX	
Plugs								
0000		Vertical, Rear Wire Entry	· ·			39513-20XX	39900-02XX	
		Vertical with Retention Screws, Rear Wire Entry				39517-20XX	39900-17XX	
	2 01 / 150"\	Vertical, Front Wire Entry	8.0A	16 to 30 AWG	2 to 20	39513-30XX	39900-03XX	
	3.81mm (.150")	Vertical with Retention Screws, Front Wire Entry	6.UA		2 10 20	39517-30XX	39900-18XX	
		Horizontal		16 to 24 AWG		39510-00XX	N/A	
10000 P		Horizontal with Retention Screws		10 IU 24 AWU		39514-00XX	N/A	

Replace XX with circuit sizes 02 to 20.

	Pitch	Description	Current	Wire Range	Circuits		er No.
			PCB Headers			ESE	Beau®
		Vertical, Open Ends		N/A	2 to 24	39521-00XX	39870-04XX
A STATE OF THE STA		Vertical, Closed Ends				39521-10XX	39870-05XX
THE PARTY OF THE P		Vertical, Surface Mount Compatible				39521-40XX	39870-13XX
		Vertical with Threaded Retention Inserts				39525-00XX	39870-11XX
The latest of th		Vertical with Threaded Retention Inserts, Surface Mount Compatible				39525-40XX	N/A
A DAME OF THE PARTY OF THE PART	5.00mm (.197")	Horizontal, Open Ends	15.0A			39522-00XX	39870-06XX
A Company of the Comp		Horizontal, Closed Ends				39522-10XX	39870-07XX
		Horizontal, Surface Mount Compatible				39522-40XX	39870-14XX
		Horizontal with Threaded Retention Inserts				39526-00XX	39870-12XX
		Horizontal with Threaded Retention Inserts, Surface Mount Compatible				39526-40XX	
		Dual Level, Open Ends			4 to 48	39528-00XX*	N/A
2.500			Plugs			1	
		Vertical, Rear Wire Entry	15.0A	- 12 to 26 AWG	2 to 24	39523-20XX	39870-02XX
		Vertical with Retention Screws, Rear Wire Entry	10.0A			39527-20XX	N/A
	5 00 (107")	Vertical, Front Wire Entry	15.0A			39523-30XX	39870-03XX
	5.00mm (.197")	Vertical with Retention Screws, Front Wire Entry	10.0A			39527-30XX	N/A
		Horizontal	15.04			39520-00XX	39870-01XX
		Horizontal with Retention Screws	15.0A			39524-00XX	N/A

Replace XX with circuit sizes 02 to 24.
*Dual level PCB header available in circuit sizes 04 to 48.

	Pitch	Description	Current	Wire Range	Circuits		er No.
		·	CB Headers	3		ESE	Beau®
		Vertical, Open Ends	15.0A	N/A		39531-00XX	39860-04XX
		Vertical, Closed Ends				39531-10XX	39860-05XX
MARA		Vertical, Surface Mount Compatible				39531-40XX	39860-13XX
		Vertical with Threaded Retention Inserts				39535-00XX	39860-11X)
AAA O		Vertical with Threaded Retention Inserts, Surface Mount Compatible			2 to 24	39535-40XX	39860-15X)
MAN	5.08mm (.200")	Horizontal, Open Ends			2 10 24	39532-00XX	39860-06X)
		Horizontal, Closed Ends				39532-10XX	39860-07X)
		Horizontal, Surface Mount Compatible				39532-40XX	39860-14X
		Horizontal with Threaded Retention Inserts				39536-00XX	39860-12X
		Horizontal with Threaded Retention Inserts, Surface Mount Compatible				39536-40XX	39860-16X
		Dual Level, Open Ends			4 to 48	39538-00XX*	39860-08X
0.086			Plugs				
		Vertical, Rear Wire Entry	15.0A	12 to 26 AWG	2 to 24	39533-20XX	39860-02X
		Vertical with Retention Screws, Rear Wire Entry	10.0A			39537-20XX	N/A
		Vertical, Front Wire Entry	15.0A			39533-30XX	39860-03X
	5.08mm (.200")	Vertical with Retention Screws, Front Wire Entry	10.0A			39537-30XX	N/A
		Horizontal				39530-00XX	39860-01X
		Horizontal Plug with Retention Screw	15.0A			39534-00XX	39860-10X

Replace XX with circuit sizes 02 to 24.
*Dual level PCB header available in circuit sizes 04 to 48.



Bringing People & Technology Together, WorldwideSM

Americas Headquarters Lisle, Illinois 60532 U.S.A.

1-800-78MOLEX amerinfo@molex.com

Far East North Headquarters

Yamato, Kanagawa, Japan 81-462-65-2324 feninfo@molex.com

Far East South Headquarters

Jurong, Singapore 65-6-268-6868 fesinfo@molex.com

European Headquarters

Munich, Germany 49-89-413092-0 eurinfo@molex.com

Corporate Headquarters 2222 Wellington Ct. Lisle, IL 60532 U.S.A. 630-969-4550 Fax:630-969-1352