



<誤嵌合防止キー (極性) タイプ> <POLARITY KEY TYPE>

| 51239-2001 | 51239-2002 | 51239-2003 | 51239-2004 | 51239-2005 |
|---------------|------------|------------|------------|------------|
| | | | | |
| STANDARD TYPE | A TYPE | B TYPE | C TYPE | D TYPE |

| TOLERANCES: | |
|-------------|-------|
| 10 UNDER | ±0.2 |
| 10 OVER | ±0.25 |
| 30 UNDER | ±0.3 |
| ANGLE | ±3° |

| C-4 | D | 51239-2005 | 51239-**0* | 20 |
|---------------------------------|---------------|--------------|------------|---------|
| C-3 | C | 51239-2004 | | |
| B-3 | B | 51239-2003 | | |
| B-2 | A | 51239-2002 | | |
| — | STANDARD | 51239-2001 | | |
| POLARITY POSITION (CIRCUIT No.) | POLARITY TYPE | MATERIAL No. | MODEL No. | CIRCUIT |

注記
NOTES

- 材質
MATERIAL
ガラス入りPBT樹脂 UL94V-0 色:黒
HOUSING : PBT G.F. UL94V-0 COLOR : BLACK
- 適用端子 : 56120-8*90 , 56121-8*90
APPLICABLE CRIMP PIN : 56120-8*90 , 56121-8*90
- 適用シェルボディ : 56380-2000
APPLICABLE SHELL BODY : 56380-2000
- 適用シェルカバー : 56381-2000
APPLICABLE SHELL COVER : 56381-2000
- 嵌合相手 : 51233-201*
MEET WITH : 51233-201*

| DRAWING CORRECTION | QUALITY SYMBOLS |
|---|-----------------|
| EC NO: PG2017-0285 DRAWN: BRUPERT 2016/09/14 CHKD: BWOODMAN 2016/09/16 APPR: BWOODMAN 2016/09/16 | ▽=0 ▽=0 |
| B | DESCRIPTION |

| GENERAL TOLERANCES (UNLESS SPECIFIED) | |
|--|-------------|
| | mm INCH |
| 4 PLACES | ± --- ± --- |
| 3 PLACES | ± --- ± --- |
| 2 PLACES | ± --- ± --- |
| 1 PLACE | ± --- ± --- |
| 0 PLACE | ± --- ± --- |
| ANGULAR ± 5° | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | |

| DIMENSION STYLE | |
|-----------------|------------|
| MM ONLY | |
| DRAWN BY | DATE |
| BRUPERT | 2016/09/14 |
| CHECKED BY | DATE |
| APPROVED BY | DATE |
| BWOODMAN | 2016/09/16 |
| MATERIAL NO. | |
| AS NOTED | |
| SIZE | B |

| SCALE | DESIGN UNITS | THIRD ANGLE PROJECTION |
|---|--------------|------------------------|
| 2:1 | METRIC | ◎ |
| TITLE | | |
| COMPACT ROBOT CONN.(CRC) PLUG SOCKET HS'G | | |
| DOCUMENT NO. | | |
| SD-51239-005 | | |
| SHEET NO. | | |
| 1 OF 1 | | |