

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0734152863](#)  
**Status:** **Active**  
**Overview:** [FAKRA PCB, Cable and Sealed Connection Systems](#)  
**Description:** 50 Ohms, FAKRA/SMB Right-Angle, Printed Circuit Board, Bulkhead Double Flange, Kinked Tail, Jack Receptacle, Code D/Bordeaux Violet

**Documents:**

[3D Model](#) [3D Model \(PDF\)](#)  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**General**

|                 |  |
|-----------------|--|
| Product Family  | RF/Coax Connectors   |
| Series          | <a href="#">73415</a>  |
| Application     | Automotive   |
| Overview        | <a href="#">FAKRA PCB, Cable and Sealed Connection Systems</a> |
| Product Name    | FAKRA, SMB   |
| Style           | PCB  |
| Type            | Subminiature   |
| UPC             | 800756484433   |
| Wire/Cable Type | N/A  |

**Physical**

|                             |                           |
|-----------------------------|---------------------------|
| Gender                      | Jack                      |
| Keying to Mating Part       | Yes                       |
| Net Weight                  | 6.493/g                   |
| Orientation                 | Right Angle               |
| PCB Mounting                | Through Hole - Kinked Pin |
| PCB Thickness - Recommended | 2.60mm                    |
| Packaging Type              | Tray                      |
| Panel Mount                 | Yes                       |
| Panel Mount Method          | Bulkhead                  |
| Reverse Polar               | No                        |

**Electrical**

|                 |                             |
|-----------------|-----------------------------|
| Frequency       | 4 GHz                       |
| Impedance       | 50Ω                         |
| Power / Voltage | VOLTAGE: 335 Vrms@Sea Level |

**Solder Process Data**

|  |          |
|--|----------|
| Duration at Max. Process Temperature (seconds) | 010      |
| Lead-freeProcess Capability                    | SMC&WAVE |
| Max. Cycles at Max. Process Temperature        | 002      |
| Process Temperature max. C                     | 260      |

**Material Info**

**Reference - Drawing Numbers**

|               |              |
|---------------|--------------|
| Sales Drawing | SD-73415-286 |
|---------------|--------------|



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant with Exemption 6(c)**

**REACH SVHC**

Not Contained Per -ED/88/2018 (15 January 2019)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

50 Image

Not Relevant

Not Contained

**Search Parts in this Series**

[73415 Series](#)