

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [75102-0079](#)  
**Status:** **Active**  
**Description:** 2.54mm Pitch C-Grid® Breakaway Header, Dual Row, Vertical, Compliant Pin, 4 Circuits, Tin (Sn) Plating

**Documents:**

[3D Model](#) [Product Specification PS-75100-001 \(PDF\)](#)  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**


CSA LR19980  
 UL E29179

**General**

Product Family PCB Headers  
 Series [75102](#)  
 Application Board-to-Board, Signal, Wire-to-Board  
 Application Tooling Part Link [622021901](#)  
 Application Tooling Part Link [622021903](#)  
 Application Tooling Part Link [622021904](#)  
 Application Tooling Part Link [622021910](#)  
 Application Tooling Part Link [622021920](#)  
 Application Tooling Part Link [622021930](#)  
 Application Tooling Part Link [622021940](#)  
 Application Tooling Part Link [622021950](#)  
 Application Tooling Part Link [622021960](#)  
 Product Name C-Grid®

**Physical**

Breakaway Yes  
 Circuits (Loaded) 4  
 Circuits (maximum) 4  
 Color - Resin Black  
 Durability (mating cycles max) 25  
 Flammability 94V-0  
 Glow-Wire Compliant No  
 Lock to Mating Part None  
 Material - Metal High Performance Alloy (HPA)  
 Material - Plating Mating Tin  
 Material - Plating Termination Tin  
 Material - Resin High Temperature Thermoplastic  
 Number of Rows 2  
 Orientation Vertical  
 PC Tail Length 4.75mm  
 PCB Locator No  
 PCB Retention Yes  
 PCB Thickness - Recommended 2.40mm  
 Packaging Type Bag  
 Pitch - Mating Interface 2.54mm  
 Polarized to Mating Part Yes  
 Shrouded Fully  
 Stackable Yes  
 Surface Mount Compatible (SMC) Yes  
 Temperature Range - Operating -40°C to +105°C  
 Termination Interface: Style Through Hole - Compliant Pin



Series

image - Reference only

**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC Contains SVHC: No**  
**Low-Halogen Status Low-Halogen**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[75102Series](#)

**Mates With**

[70066](#) , [71973](#) , [7859](#) , [70400](#) , [70192](#) , [71850](#) , [71395](#) , [70854](#) , [71979](#) , [70450](#)

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

Description	Product #
CPI Modular Insertion Pin	<a href="#">0622021901</a>
CPI Modular Left End Spacer	<a href="#">0622021903</a>
CPI Modular Right End Spacer	<a href="#">0622021904</a>
Modular Press In Tool, 4 Circuits	<a href="#">0622021910</a>
Modular Press In Tool, 6 Circuits	<a href="#">0622021920</a>

**Electrical**

Current - Maximum per Contact

3A

Voltage - Maximum

250V

**Material Info****Reference - Drawing Numbers**

Product Specification

PS-75100-001

Sales Drawing

SD-75102-001

Modular Press In 0622021930

Tool, 10 Circuits

Modular Press In 0622021940

Tool, 20 Circuits

Modular Press In 0622021950

Tool, 40 Circuits

Modular Press In 0622021960

Tool, 80 Circuits

This document was generated on 04/03/2012

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**