



- NOTES:  
 1. MATERIAL: SEE TABLE  
 2. FINISHES: SEE TABLE  
 3. PACKAGING: CLEAR POLY BAG  
 4. MATES WITH: RJ-45 FEMALE AND 15 PIN D-SUB FEMALE

MATERIAL NO.	LENGTH
849013011	.6M +13mm-0 [ 2'0" +.50"-0"]
849013012	2M +42mm-0mm [ 6'7" +1.65"-0"]
849013013	5M +102mm-0mm [ 16'5" +4.00"-0"]
849013014	10M +152mm-0mm [ 32'10" +6.00"-0"]
849013015	15M +152mm-0mm [ 49'2" +6.00"-0"]

P1	P2	SIGNAL
1	1	+24V
2	2	TRIGGER +
3	3	TRIGGER -
4	4	LINE 0
5	5	LINE 1
6	6	LINE 2
7	7	LINE 3
8	8	GROUND
9	9	NOT USED
10	10	NOT USED
11	11	NOT USED
12	12	NOT USED
13	13	NOT USED
14	14	NOT USED
15	15	NOT USED

ITEM	QTY	DESCRIPTION	MATERIAL	FINISH
6	8	CONTACT PIN	BRASS	GOLD PLATED
5	1	CONNECTOR SHIELDING KIT	AS SUPPLIED	VENDOR SPEC.
4	1	LABEL	MYLAR	BLACK/CHROME
3	1	RJ-45 PLUG, SHIELDED, KEYED	PH. BRNX. CONT.	GOLD PLATED
2	A/R	OVERMOLD, 90 DEG.	PVC	YELLOW
1	1	CABLE, 4P, SHIELDED	PVC JACKET	BLACK

ADDED GULLWING EC NO: ETC2006-0080 2005/11/18 DRWR:RSTONE 2005/11/21 CHKDR: DEROSS 2005/11/22 APPR:RDEROSS	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION																											
	$\nabla=0$ $\nabla=0$	<table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>3 PLACES</td> <td>± ---</td> <td>±.005</td> </tr> <tr> <td>2 PLACES</td> <td>±0.13</td> <td>±.01</td> </tr> <tr> <td>1 PLACE</td> <td>±0.25</td> <td>± ---</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	±.005	2 PLACES	±0.13	±.01	1 PLACE	±0.25	± ---	<table border="1"> <thead> <tr> <th>DRAWN BY</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>R.STONE</td> <td>09-21-05</td> </tr> <tr> <th>CHECKED BY</th> <th>DATE</th> </tr> <tr> <td>R.DEROSS</td> <td>10-25-05</td> </tr> <tr> <th>APPROVED BY</th> <th>DATE</th> </tr> <tr> <td>R.DEROSS</td> <td>10-25-05</td> </tr> </tbody> </table>	DRAWN BY	DATE	R.STONE	09-21-05	CHECKED BY	DATE	R.DEROSS	10-25-05	APPROVED BY	DATE	R.DEROSS	10-25-05	1:1	INCH	
		mm	INCH																														
	4 PLACES	± ---	± ---																														
3 PLACES	± ---	±.005																															
2 PLACES	±0.13	±.01																															
1 PLACE	±0.25	± ---																															
DRAWN BY	DATE																																
R.STONE	09-21-05																																
CHECKED BY	DATE																																
R.DEROSS	10-25-05																																
APPROVED BY	DATE																																
R.DEROSS	10-25-05																																
REV	DESCRIPTION	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	<table border="1"> <thead> <tr> <th>MATERIAL NO.</th> <th>DOCUMENT NO.</th> <th>SHEET NO.</th> </tr> </thead> <tbody> <tr> <td>SEE CHART</td> <td>SD-84901-018</td> <td>1 OF 1</td> </tr> </tbody> </table>	MATERIAL NO.	DOCUMENT NO.	SHEET NO.	SEE CHART	SD-84901-018	1 OF 1	TITLE <b>CORD ASSEMBLY, 90 DEG RJ-45, KEYED, TO D-SUB</b>																							
MATERIAL NO.	DOCUMENT NO.	SHEET NO.																															
SEE CHART	SD-84901-018	1 OF 1																															