



REV	DESCRIPTION	DATE
B	ENTER DESCRIPTION	2005/12/01
	EC NO: I2006-0310	2005/12/01
	DRWN:SSUDHIR	2005/12/02
	CHKD:KPRASAD	2005/12/02
	APPR:KPRASAD	2005/12/02

QUALITY SYMBOLS	DESCRIPTION
▽=0	
△=0	

GENERAL TOLERANCES (UNLESS SPECIFIED)	
mm	INCH
4 PLACES ± ---	± ---
3 PLACES ± ---	± ---
2 PLACES ± ---	± ---
1 PLACE ± ---	± ---
ANGULAR ± 2 °	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE	
MM ONLY	
DRAWN BY	DATE
SH	2002/19/10
CHECKED BY	DATE
GJ	2002/19/10
APPROVED BY	DATE
GJ	2002/19/10
MATERIAL NO.	-----

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
2:1	METRIC	
TITLE		
128 POS MALE CONNECTOR DIN 41612 STYLE R (C-PIN) DIMENSIONS		
MOLEX MOLEX INCORPORATED		
DOCUMENT NO.	SHEET NO.	
SDA-85015-0001	3 OF 3	

VIEW ON MATING SIDE



A = 116 STANDARD CONTACTS L=2  
 Z = 12 FMLB CONTACTS + 1.0 L=2  
 S = 128 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/0 = CONTACT AREA PERFORM. LEVEL 2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SDA-85015-0001 SHT 3
TECHNICAL DATA	PS-85013-0002

CONTACT SYMBOL	PERFORM. LEVEL	CONTACT POSITION NUMBER
A	G2/0	a4-a32, b4-b32, c4-c32, d4-d32
Z	G2/0	a1-a3, b1-b3, c1-c3, d1-d3

ENTER DESCRIPTION EC NO: I2006-0310 DRWN:SSUDHIR 2005/12/01 CHKD:KPRASAD 2005/12/02 APPR:KPRASAD 2005/12/02	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± .005</td> <td>± .0004</td> </tr> <tr> <td>3 PLACES</td> <td>± .005</td> <td>± .0004</td> </tr> <tr> <td>2 PLACES</td> <td>± .005</td> <td>± .0004</td> </tr> <tr> <td>1 PLACE</td> <td>± .005</td> <td>± .0004</td> </tr> <tr> <td colspan="2">ANGULAR</td> <td>± .0004°</td> </tr> </table>		mm	INCH	4 PLACES	± .005	± .0004	3 PLACES	± .005	± .0004	2 PLACES	± .005	± .0004	1 PLACE	± .005	± .0004	ANGULAR		± .0004°	DIMENSION STYLE MM ONLY	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
		mm	INCH																					
	4 PLACES	± .005	± .0004																					
	3 PLACES	± .005	± .0004																					
2 PLACES	± .005	± .0004																						
1 PLACE	± .005	± .0004																						
ANGULAR		± .0004°																						
DRAWN BY SH	DATE 2002/19/10	TITLE 128 POS MALE CONNECTOR DIN 41612 STYLE R CONTACTS ARRANGEMENT																						
CHECKED BY GJ	DATE 2002/19/10	MOLEX INCORPORATED																						
APPROVED BY GJ	DATE 2002/19/10	MATERIAL NO. 85015-9004	DOCUMENT NO. SDA-85015-9004	SHEET NO. 1 OF 1																				

DRAFT WHERE APPLICABLE  
 MUST REMAIN  
 WITHIN DIMENSIONS

SIZE  
 A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION