

PRIMARY: 1004220701 (F3401S-6.65-N)

Use capacitance gauge and run FFT

1. SRL: VoP : 70%; Core Dia.: 0.0063; Outer Dia.: 0.0196"
2. Display SRL: X-Axis: 0-25 GHz; Y-Axis: -50 to 0 dB
3. Display Spectrograph: Y-Axis (SRL Freq. Range): 1-25 GHz; Value Range (Color Spectrum): -35 to -20
4. Flag if Spectrograph is showing solid color <-32 dB

Engineering to determine if Wire Straighteners are needed.

LONGITUDINAL FOIL SHIELD: 1000680079

TDR & VNA CHECK

1 start sample per spool. Length = 6ft 7in. (2m)

HEAT SEALED SEPARATOR (LAYER 1)

LAY LENGTH (LH) / ANGLE / OVERLAP

0.100" / 46 degrees / 42%

HEAT SEALED SEPARATOR (LAYER 2)

PRINT LEGEND: MOLEX TEMP-FLEX(R) <LOCATION CODE: US or PHL or GDL > TWINMAX(TM) 34 AWG 1000680079 --- E61522
 <UL CODE: -MPI for PHL, <blank> for US, -MDM for GDL> STYLE 22046 cRUus AWM I A/B 105C 30V FT1 VW-1 --- <TRACEABILITY>

<TRACEABILITY> = Lot/Batch #, Mfg. Date (format: YYYYMMDD) Sequential Footage Marking

LAY LENGTH (RH) / ANGLE / OVERLAP

0.100" / 46 degrees / 42%

LENGTHS REQUIRED	LENGTHS PER SPOOL	MIN. LENGTH	SPLICE CODE	SPOOL SIZE
Any	1	500'	N/A	12X7X5