

PRIMARY: 1004221448

Use capacitance gauge and run FFT:

1. SRL: VoP: 70%; Core Dia.: 0.0107"; Outer Dia.: 0.035"
2. Display SRL: X-Axis: 0-25 GHz; Y-Axis: -50 to 0 dB
3. Display Spectrograph: Y-Axis (SRL Freq. Range): 1-25 GHz; Value Range (Color Spectrum): -35 to -20
4. Flag if Spectrograph is showing solid color <-32 dB

LONGITUDINAL FOIL SHIELD: 1000680107

TDR & VNA CHECK

1 start sample per spool. Length = 9ft 10.3 in. (3m)

HELICAL HEAT-SEALED SEPARATOR

HEAT SEALING required. (Adhesive Side IN)

LAY LENGTH (LH) / ANGLE / OVERLAP

0.130" / 58 degrees / 37%

HELICAL HEAT-SEALED JACKET

HEAT SEALING required. (Adhesive Side In)

Print Legend: MOLEX TEMP-FLEX(R) <LOCATION CODE: US or PHL or GDL>TWINMAX(TM) 30 AWG 1000680107
 --- E61522 <UL CODE: -MPI for PHL, <blank> for US, -MDM for GDL> STYLE 22058 cRUus AWM I A/B 105C 30V FT1 ---
 <TRACEABILITY>

<TRACEABILITY> = Lot/Batch #, Mfg. Date <format: YYYYMMDD> Sequential Footage Marking

LAY LENGTH (RH) / ANGLE / OVERLAP

0.130" / 58 degrees / 37%

LENGTHS REQUIRED	LENGTHS PER SPOOL	MIN. LENGTH	SPLICE CODE	SPOOL SIZESPOOL
Any	1	1000'	NA	12" Plastic