



8 WIRE

Pin No.	Wire
1	White
2	Brown
3	Green
4	Yellow
5	Grey
6	Pink
7	Blue
8	Red

PART No MATRIX

8	0	8	0	0	0	P	0	2	X	X	X	X	X	X	
8=Micro Change	0=Portable	8=8 Core	000 = Female Straight			Cable-PUR, 8 x 0.25mm			M=Metres F=Feet	LENGTH 020=2 METRES 050=5 METRES 200=20 METRES				Coupling Nut Material Blank=Standard 1=Stainless Steel 5=Delrin	
															Blank=Yellow (Standard) A=Grey

Specification.

(See alternative variations in matrix key)
 Insert Material - PUR (30% Glass Filled)
 Contact Material - Brass (CuZn36)
 Contact Plating - 2um Ni, 0.70um Gold
 Coupling Nuts - Nickel Plated Brass
 Seal - Viton O-Ring
 Protection Class - IP68
 Voltage Rating - 30 VAC / 36 VDC
 Contact Current Rating - 4 Amps
 Overmoulding - PUR

N/A	Rev	By	Descriptions	Date	Approved
N/A	A	GG	First Issue	13.05.04	GG
ECN	Rev	By	Descriptions	Date	Approved

This drawing and its contents are the proprietary and confidential property of Woodhead Industries Inc. and/or its subsidiaries and may not be used or disclosed to others without the express prior written consent of Woodhead Industries Inc. and/or its subsidiaries.

Part No.	808000P02MXXX	Size	A4
Description	MICRO CHANGE 80 SERIES CONNECTOR LEAD		
Applicable Standards	ASME Y14.5M ISO 1660		
Drawn	G.GREEN	DATE	13.05.04
Checked	N.WITTS	DATE	13.05.04
Approved	N.WITTS	DATE	13.05.04
Material	SEE SPECIFICATION		
Finish	SEE SPECIFICATION		
Dimensions In MM	0.0 ± 0.25mm 0.00 ± 0.10mm 0.000 ± 0.025mm Angles ± 1°		
Drawing No.	808000P02MXXX	Rev	A
Scale	NTS SHEET 1 OF 1		

Third Angle Projection