

## This document was generated on 07/26/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 001	15977084			
Status: Act	tive			
Overview: Mini-	-Fit TPA2 Plugs and Rec	eptacles		
Description: Mini-				
	uits, Gold (Au) Plating, wi			
-				
Documents:				
3D Model		Packaging Specification PK-30069-001-001 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
Product Specification PS-55				
Floude Specification FS-55	<u>30-003 (FDF)</u>		Series image	e - Reference only
Agency Certification				
CSA		LR19980	EU ELV	
UL		E29179	Not Relevant	
			EU RoHS	China RoHS
General				China Rons
Product Family		PCB Headers	Compliant	
Series		<u>30069</u>	REACH SVHC	
Application		Power, Wire-to-Board	Not Contained Per	
Comments		Current for wire-to-wire applications = 13.0A max. per	-ED/01/2017 (12	
		circuit. Current for wire-to-board applications = 9.0A	January 2017)	
		max. per circuit	Halogen-Free	
Overview		Mini-Fit TPA2 Plugs and Receptacles	<u>Status</u>	
Product Name		Mini-Fit® TPA	Not Low-Halogen	
UPC		800754912754	Need more information	ation on product
UFC		800754912754	environmental con	-
Physical			Email productcompl	ianco@molox.com
Breakaway		No		
Circuits (Loaded)		8		tact Us section for any
Circuits (maximum)		8	non-product complia	ance questions.
Color - Resin		Black	China ROHS	Green Image
Durability (mating cycles max)		30	ELV	Not Relevant
First Mate / Last Break		No	RoHS Phthalates	Not Contained
Flammability		94V-0		Not Contained
Glow-Wire Compliant		No		
Guide to Mating Part		No		
Keying to Mating Part		None	Search Parts in t	his Series
Lock to Mating Part		Yes	30069 Series	
Material - Metal		Brass		
Material - Plating Mating		Gold	Motoo With	
Material - Plating Mating Material - Plating Termination		Tin	Mates With	ATM Desertable Lines
	лт			A <sup>™</sup> Receptacle Housing
Material - Resin		Polyester		
Net Weight		2.560/g	Use With	
Number of Rows		2	Mini-Fit® TPA Re	ceptacle Housing <u>30071</u>
Orientation		Vertical	30072	
PCB Locator		Yes		
PCB Retention		Yes		
PCB Thickness - Recommended		1.80mm		
Packaging Type		Bag		
Pitch - Mating Interface		4.20mm		
Pitch - Termination Interface		4.20mm		
Plating min - Mating		0.762µm		
Plating min - Termination		2.540µm		
Polarized to Mating Part		Yes		
Polarized to PCB		Yes		
Shrouded		Partial		
Stackable		No		
JIAUNADIE				

Surface Mount Compatible (SMC) Temperature Range - Operating Termination Interface: Style	No -40°C to +105°C Through Hole	
Electrical Current - Maximum per Contact Voltage - Maximum	13.0A 600V	
Solder Process Data Lead-freeProcess Capability	WAVE	
<b>Material Info</b> Engineering Number	30069-08A2	
<b>Reference - Drawing Numbers</b> Packaging Specification Product Specification Sales Drawing	PK-30069-001-001 PS-5556-003 SDA-30069-****	

## This document was generated on 07/26/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Authorized Distributor

Click to view similar products for Headers & Wire Housings category:

<u>5-87631-1</u> 0009523102 008383010000010 609-1030 6-146309-3 6437006-5 644457-9 M80-4802005 M80-5121842 M80-6812001