


Distributed by:

**JAMECO**<sup>®</sup>  
ELECTRONICS

**www.Jameco.com ♦ 1-800-831-4242**


The content and copyrights of the attached  
material are the property of its owner.

Jameco Part Number 460832



**Vibrakrimp® Butted Seam With Vibration Support**

Tab Size	Wire Range AWG (mm <sup>2</sup> )	Dimension		Loose Piece Order No.	Mylar Tape Order No.	Insulation Diameter Range	Max. Length L
		Max. Width W	Grip G				
6.30 by 0.80 (.250 by .032)	18-22 (0.80-0.35)	7.60 (.301)	7.90 (.310)	19018-0005	19018-0006	1.50/3.20 (.060/.125)	20.40 (.802)
	14-16 (2.00-1.30)	7.60 (.301)	7.90 (.310)	19018-0014	19018-0015	2.10/3.70 (.085/.145)	20.40 (.802)
	12-14 (3.30-2.00)	7.60 (.301)	7.90 (.310)	19018-0024	19018-0025	2.50/4.40 (.100/.175)	20.40 (.802)
	10-12 (5.00-3.30)	7.70 (.305)	7.90 (.310)				
4.70 by 0.80 (.187 by .032)	24-26 (0.20-0.12)	6.00 (.238)	6.30 (.250)	19018-0045	19018-0046	1.00/2.40 (.040/.095)	17.50 (.690)
	18-22 (0.80-0.35)	6.00 (.238)	6.30 (.250)	19018-0002	19018-0003	1.50/3.20 (.060/.125)	18.20 (.717)
	12-14 (3.30-2.00)	6.00 (.238)	6.30 (.250)	19018-0022	19018-0023	2.50/4.40 (.100/.175)	18.20 (.717)
4.70 by 0.50 (.187 by .020)	24-26 (0.20-0.12)	6.00 (.238)	6.30 (.250)	19018-0044	19018-0047	1.00/2.40 (.040/.095)	17.50 (.690)
	18-22 (0.80-0.35)	6.00 (.238)	6.30 (.250)	19018-0001	19018-0004	1.50/3.20 (.060/.125)	18.20 (.717)
	14-16 (2.00-1.30)	6.00 (.238)	6.30 (.250)	19018-0011	19018-0013	2.20/3.70 (.085/.145)	18.20 (.717)
	24-26 (0.20-0.12)	4.10 (.163)	6.30 (.250)	19018-0020	19018-0048	1.00/2.40 (.040/.095)	17.50 (.690)
2.80 by 0.80 (.110 by .032)	18-22 (0.80-0.35)	4.10 (.163)	6.30 (.250)			1.50/3.20 (.060/.125)	18.20 (.717)
	14-16 (2.00-1.30)	4.10 (.163)	6.30 (.250)	19018-0017	19018-0018	2.20/3.70 (.085/.145)	18.20 (.717)
	24-26 (0.20-0.12)	4.10 (.163)	6.30 (.250)	19018-0019		1.00/2.40 (.040/.095)	17.50 (.690)
2.80 by 0.50 (.110 by .020)	18-22 (0.80-0.35)	4.10 (.163)	6.30 (.250)	19018-0007	19018-0010	1.50/3.20 (.060/.125)	18.20 (.717)
	14-16 (2.00-1.30)	4.10 (.163)	6.30 (.250)	19018-0016		2.20/3.70 (.085/.145)	18.20 (.717)



**Avikrimp® Nylon Insulated With Vibration Support**

Tab Size	Wire Range AWG (mm <sup>2</sup> )	Dimension		Loose Piece Order No.	Mylar Tape Order No.	Max. Wire Insulation Dia.	Max. Length L
		Max. Width W	Grip G				
6.30 by 0.80 (.250 by .032)	18-22 (0.80-0.35)	7.60 (.301)	7.90 (.310)	19019-0012	19019-0013	2.90 (.115)	22.00 (.865)
	14-16 (2.00-1.30)	7.60 (.301)	7.90 (.310)	19019-0031	19019-0033	3.50 (.138)	22.00 (.865)
	12-14 (3.30-2.00)	7.60 (.301)	7.90 (.310)	19019-0052	19019-0054	4.30 (.170)	22.00 (.865)
	10-12 (5.00-3.30)	7.70 (.305)	7.90 (.310)	19019-0037	19019-0038	5.70 (.225)	25.70 (1.011)
4.70 by 0.80 (.187 by .032)	24-26 (0.20-0.12)	6.00 (.238)	6.30 (.250)	19019-0044	19019-0045	1.80 (.072)	17.60 (.694)
	18-22 (0.80-0.35)	6.00 (.238)	6.30 (.250)	19019-0008	19019-0009	2.90 (.115)	20.00 (.789)
	14-16 (2.00-1.30)	6.00 (.238)	6.30 (.250)	19019-0028	19019-0029	3.50 (.138)	20.00 (.789)
4.70 by 0.50 (.187 by .020)	24-26 (0.20-0.12)	6.00 (.238)	6.30 (.250)	19019-0049	19019-0050	4.30 (.170)	20.00 (.789)
	18-22 (0.80-0.35)	6.00 (.238)	6.30 (.250)	19019-0043	19019-0046	1.80 (.072)	17.60 (.694)
	14-16 (2.00-1.30)	6.00 (.238)	6.30 (.250)	19019-0006	19019-0011	2.90 (.115)	20.00 (.789)
	12-14 (3.30-2.00)	6.00 (.238)	6.30 (.250)	19019-0027	19019-0030	3.50 (.138)	20.00 (.789)
5.20 by 0.80 (.205 by .032)	24-26 (0.20-0.12)	6.00 (.238)	6.30 (.250)	19019-0048	19019-0051	4.30 (.170)	20.00 (.789)
	18-22 (0.80-0.35)	6.40 (.251)	6.30 (.250)	19019-0015	19019-0058	2.90 (.115)	20.00 (.789)
	14-16 (2.00-1.30)	6.40 (.251)	6.30 (.250)	19019-0035	19019-0063	3.50 (.138)	20.00 (.789)
5.20 by 0.50 (.205 by .020)	18-22 (0.80-0.35)	6.40 (.251)	6.30 (.250)	19019-0014	19019-0016	2.90 (.115)	20.00 (.789)
	14-16 (2.00-1.30)	6.40 (.251)	6.30 (.250)	19019-0034	19019-0064	3.50 (.138)	20.00 (.789)
2.80 by 0.80 (.110 by .032)	24-26 (0.20-0.12)	4.10 (.163)	6.30 (.250)	19019-0041	19019-0042	1.80 (.072)	17.60 (.694)
	18-22 (0.80-0.35)	4.10 (.163)	6.30 (.250)	19019-0004	19019-0005	2.90 (.115)	20.00 (.789)
	14-16 (2.00-1.30)	4.10 (.163)	6.30 (.250)	19019-0025	19019-0026	3.50 (.138)	20.00 (.789)
2.80 by 0.50 (.110 by .020)	24-26 (0.20-0.12)	4.10 (.163)	6.30 (.250)	19019-0039	19019-0040	1.80 (.072)	17.60 (.694)
	18-22 (0.80-0.35)	4.10 (.163)	6.30 (.250)	19019-0001	19019-0003	2.90 (.115)	20.00 (.789)
	14-16 (2.00-1.30)	4.10 (.163)	6.30 (.250)	19019-0022	19019-0024	3.50 (.138)	20.00 (.789)