



製品番号  
ENG. NO.

回路番号  
CIRCUIT NO.

注記  
NOTE

使用ターミナル: ENG. NO. 5103\*  
APPLICABLE TERMINAL: ENG. NO. 5103\*

	47.5	51	22-01-1204	5102-20	20
	45	48.5	▲ -1194	▲ -19	19
	42.5	46	-1184	-18	18
	40	43.5	-1174	-17	17
	37.5	41	-1164	-16	16
	35	38.5	-1154	-15	15
	32.5	36	-1144	-14	14
	30	33.5	-1134	-13	13
	27.5	31	-1124	-12	12
	25	28.5	-1114	-11	11
	22.5	26	-1104	-10	10
	20	23.5	-1094	-09	9
	17.5	21	-1084	-08	8
	15	18.5	-1074	-07	7
	12.5	16	-1064	-06	6
	10	13.5	-1054	-05	5
	7.5	11	-1044	-04	4
	5	8.5	▼ -1034	▼ -03	3
	2.5	6	22-01-1024	5102-02	2
	B	A	EDP. NO.	ENG. NO.	NO. OF EXTS.

材料  
MATERIAL  
ナイロン66, UL94V-0  
NYLON66, UL94V-0

REVISED EC NO. J2006-347 2006/07/31 DRW:KSAI1001 CHKD:HTANAKA 2006/08/04 APPR:NIKIITA 2006/08/07	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	MOLEX INCORPORATED DOCUMENT NO. SD-5102-001 SHEET NO. 1 OF 1
	10 UNDER	±0.2	DRAWN BY H. IJIMA	DATE 1996/07/05	TITLE MINI SPOX HSG		
	10 OVER 30 UNDER	±0.25	CHECKED BY M. FUKUSHIMA	DATE 1996/07/05	THIRD ANGLE PROJECTION		
	30 OVER	±0.3	APPROVED BY M. ENOMOTO	DATE 1996/07/05	SEE CHART		
H	DESCRIPTION	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		