

This document was generated on 10/08/2014 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	39-01-2141			
Status:	Active			
ACIIVE				
Overview:	<u>Mini-Fit Jr.™ Power Con</u>			
Description:	14 Circuits	ng, Dual Row with Panel Mount Ears, UL 94V-2, Panel Mount,		
	14 Circuits			
Documents:				
3D Model		Product Specification PS-5556-001 (PDF)		
Drawing (PDF)		Packaging Specification PK-5559-001 (PDF)		
	n PS-45750-001 (PDF)	RoHS Certificate of Compliance (PDF)	Series	
			image - Reference only	
Agency Certific	ation			
CSA	ation	LR19980	EU RoHS China RoHS	
UL		E29179	ELV and RoHS	
UL		E29175	Compliant	
General			REACH SVHC	
Product Family		Crimp Housings	Contains SVHC: No	
Series		<u>5559</u>	Low-Halogen Status	
Application		Power, Wire-to-Board, Wire-to-Wire	Low-Halogen	
Comments		Current = 13A max. per circuit when header is mated	Need more information on product	
		to a receptacle loaded with <u>45750</u> series terminals	environmental compliance?	
		crimped to 16 AWG wire See Molex product	environmental compliance:	
		specification PS-45750-001 for additional current	Email productcompliance@molex.com	
		derating information Glow Wire Equivalent Part.	For a multiple part number RoHS Certificate of	
MolexKits		Yes	Compliance, <u>click here</u>	
Overview		Mini-Fit Jr.™ Power Connectors	Diagon visit the Contact Lie section for any	
Product Name		Mini-Fit Jr.™	Please visit the <u>Contact Us</u> section for any non-product compliance questions.	
UPC		800753583955	non-product compliance questions.	
Physical				
Breakaway		No		
Circuits (maximum)		14	Search Parts in this Series	
Color - Resin		Natural	5559Series	
Flammability		94V-2		
Gender		Plug	Mates With	
Glow-Wire Compliar	nt	No	5557 Dual Row Receptacle Housing	
Material - Resin		Nylon		
Net Weight		4.275/g	Use With	
Number of Rows		2	5558, 30490 Male Terminal	
Packaging Type Panel Mount		Bag Yes		
		4.20mm		
Pitch - Mating Interfa Pitch - Termination I		4.20mm		
Polarized to Mating		Yes		
Stackable		No		
Temperature Range	- Operating	-40°C to +105°C		
Electrical				
Current - Maximum	per Contact	13A		
Material Info				
Old Part Number		5559-14P		
Reference - Dra	-			
Packaging Specifica		PK-5559-001		
Product Specification	n	PS-45750-001, PS-5556-001		
Sales Drawing		SD-5559-NP		

This document was generated on 10/08/2014 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION