

This document was generated on 11/14/2014

#### PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 43680-2003

Status: Active

Overview: Sabre™ Power Connector

Description: 7.50mm Pitch Sabre™ Plug Crimp Housing, UL 94V-0, 3 Circuits, Glow Wire

Compatible

**Documents:** 

3D Model Packaging Specification PK-43680-001 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-44441-9999 (PDF) Product Literature (PDF)

## **Agency Certification**

CSA LR19980 TUV R72130381 UL E29179

#### General

Product Family Crimp Housings

Series <u>43680</u>

Application Power, Wire-to-Wire

Application Tooling Part Link 63813-0800
Comments This Molex p

This Molex product is manufactured from material that has the following ratings, tested by independent agencies: a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety; section 30 Resistance to heat and fire.<P><P>The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s).<P>If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options.

Yes


MolexKits

Overview <u>Sabre™ Power Connector</u>

Product Literature Order No 987650-5662
Product Name Sabre $^{TM}$ UPC 800754366519

#### **Physical**

Circuits (maximum) 3 Color - Resin Black Flammability 94V-0 Gender Male **Glow-Wire Compliant** Yes Keying to Mating Part Yes Lock to Mating Part Yes Material - Resin Nylon Net Weight 4.621/g Number of Rows



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen



# Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

### Search Parts in this Series

43680 Series

**Mates With** 44441-2003

#### **Use With**

43178 Male Crimp Terminals

#### Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

#### Global

Tool

DescriptionProduct #Manual Extraction0638130800

Packaging Type Bag
Panel Mount No
Pitch - Mating Interface 7.50mm
Polarized to Mating Part Yes
Stackable No

Temperature Range - Operating -40°C to +75°C

**Electrical** 

Current - Maximum per Contact 18A

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification PK-43680-001

Product Specification PS-44441-9999, RPSX-44441-001

Sales Drawing SD-43680-\*003

This document was generated on 11/14/2014

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION