

This document was generated on 10/08/2013

### PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 43680-2004

Status: **Active** 

Sabre™ Power Connector **Overview:** 

7.50mm Pitch Sabre™ Plug Crimp Housing, UL 94V-0, 4 Circuits, Glow Wire **Description:** 

Compatible

**Documents:** 

Packaging Specification PK-43680-001 (PDF) 3D Model Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PSX-44441-9999 (PDF) Product Literature (PDF)

## **Agency Certification**

**CSA** LR19980 TUV R72130381 UL E29179

#### General

**Product Family** Crimp Housings

43680 Series

Application Power, Wire-to-Wire

Comments This Molex product is manufactured from material

that has the following ratings, tested by independent agencies: a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety; section 30 Resistance to heat and fire.<P><P>The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s).<P>If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options.

MolexKits Yes


Sabre™ Power Connector Overview

Product Literature Order No 987650-5662 Sabre™ **Product Name** 

**UPC** 800754366540

### **Physical**

Circuits (maximum) 4 Color - Resin Black Flammability 94V-0 Gender Male Glow-Wire Compliant Yes Keying to Mating Part Yes Lock to Mating Part Yes Material - Resin Nylon Net Weight 6.105/qNumber of Rows Packaging Type Bag



**EU RoHS ELV and RoHS** Compliant **REACH SVHC Contains SVHC: No Low-Halogen Status** Low-Halogen



#### **Need more information on product** environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series

43680Series

**Mates With** 44441-2004

**Use With** 

43178 Male Crimp Terminals

Panel Mount No
Pitch - Mating Interface 7.50mm
Polarized to Mating Part Yes
Stackable No

Temperature Range - Operating -40°C to +75°C

**Electrical** 

Current - Maximum per Contact 18A

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification PK-43680-001

Product Specification PSX-44441-9999, RPSX-44441-001

Sales Drawing SD-43680-\*004

This document was generated on 10/08/2013

# PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION