


## BU-1404940

(12 Position Male to Female Receptacle Shielded Cable Assembly, 16.4')





J2 Female

 $\begin{array}{c}
5 \\
4 \\
7 \\
8 \\
12
\end{array}$   $\begin{array}{c}
2 \\
11 \\
10 \\
12
\end{array}$ 

J1 Male

2
1
3
5
1
5
3
7
0
)
2
1
2
IELL

Mueller Electric Company 2850 Gilchrist Rd. Bld 5A Akron, OH 44305

www.muellerelectric.com

Toll Free: 800.955.2629 Phone: 330.780.2525 Fax: 330.780.2524

- Mueller's BU-1404940 is a shielded cable assembly that has a 12-position Male plug to 12-position female receptacle.
- Shell size for connector: M12 x 1.0 (A Coding)
- Cable Material: Polyurethane
  - Overall length = 16.4' (5m)
- Rating:
  - Voltage: 30V AC/DC
  - Current: 1.5 Amps
  - Standard: IEC 61076-2-101
  - Waterproof: IP67/IP68
  - Temperature: -40°C to 105°C
- RoHS 3 Compliant

Mueller Electric Company 2850 Gilchrist Rd. Bld 5A Akron, OH 44305

www.muellerelectric.com

Toll Free: 800.955.2629 Phone: 330.780.2525 Fax: 330.780.2524