


















Specification

Global Part Number	DE2E3KH222MA3B
Previous Part Number	DE1007E222M-KH
Body Dia. D	10mm max.
Lead Spacing F	7.5mm ±1.0mm
Body Thickness T	7.0mm max.
Lead Dia. phi-d	0.6mm ±0.05mm
Coating Extension e	Up to the end of crimp
TC Code	E
Capacitance Change	+20/-55%
Capacitance Change Correction	
Temp. Range for TC	-25 to +85deg.
Operating Temp. Range	-25 to +125deg. (UL std.: -25 to +85deg.)
Capacitance	2200pF ±20%
Rated Voltage	250Vac
Packaging Form	Bulk

Minimum Quantity

180mm Paper Tape	
180mm Plastic Tape	
330mm Paper Tape	
330mm Plastic Tape	
Bulk Case	
Bulk(Bag)	1000
Ammo Pack	
320Reel	
Magazine	
Box	

Details

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Features and Applctn.](#)
-  [Standard Recognition](#)
-  [Spec. and Test Methods](#)
-  [Packaging](#)
-  [Caution \(storage and operating condition\)](#)
-  [Caution \(rating\)](#)
-  [Caution \(soldering and mounting\)](#)
-  [Caution \(handling\)](#)
-  [Insertion Loss-Freq.Char.](#)
-  [Notice \(rating\)](#)
-  [Notice \(soldering and mounting\)](#)
-  [Cap.-Temp.Char.](#)
-  [Leakage Current Char.](#)
-  [Marking](#)

and are subject to change or obsolescence without notice.
Please approve our product specifications or transact the approval sheet before ordering.
Please read rating and !Cautions first.

