


## GRM21B2C1H183JA01#

Complies with RoHS Reflow OF Recommended

< List of part numbers with package codes >

 $\mathsf{GRM21B2C1H183JA01L}\ ,\ \mathsf{GRM21B2C1H183JA01K}\ ,\ \mathsf{GRM21B2C1H183JA01C}\ ,\ \mathsf{GRM21B2C1H183JA01E}$ 

Shape





"#" indicates a package specification code.

References

Packaging	Specifications	Minimum quantity
L	Embossed tape ( 180mm)	3000
К	Embossed tape ( 330mm)	10000
С	Bulk case	5000
В	Packing in bulk	1000

L size2.0 ± 0.1mmW size1.25 ± 0.1mmT size1.25 ± 0.1mmExternal terminal width e0.2 to 0.7mmDistance between external terminals g (Min.)0.7mmSize code in mm(inch)2012 (0805)		
T size   1.25 ± 0.1mm     External terminal width e   0.2 to 0.7mm     Distance between external terminals g (Min.)   0.7mm	L size	2.0 ± 0.1mm
External terminal width e   0.2 to 0.7mm     Distance between external terminals g (Min.)   0.7mm	W size	1.25 ±0.1mm
Distance between external terminals g (Min.) 0.7mm	T size	1.25 ±0.1mm
	External terminal width e	0.2 to 0.7mm
Size code in mm(inch) 2012 (0805)	Distance between external terminals g (Min.)	0.7mm
	Size code in mm(inch)	2012 (0805)

## Mass (typ.) 16mg 1 piece Reel ( 180mm) 91g

## Specifications

Capacitance	18000pF ±5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	CH(JIS)
Temperature coefficient	0 ± 60ppm/
Temperature range of temperature characteristics	20 to 125
Operating temperature range	-55 to 125

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/03/08