## GRM43ER71E475KA01# "#" indicates a package specification code.














< List of part numbers with package codes > GRM43ER71E475KA01L , GRM43ER71E475KA01K

## Shape



L W	
L size	4.5 ±0.4mm
W size	3.2 ±0.3mm
Tsize	2.5 ±0.2mm
External terminal width e	0.3mm min.
Distance between external terminals g	2.0mm min.
Size code in inch(mm)	1812 (4532M)

## References

Packaging	Specifications	Minimum quantity
L	φ180mm Embossed taping	500
К	φ330mm Embossed taping	2000

Mass (typ.)		
1 piece	160.0mg	

## **Specifications**

Capacitance	4.7μF ±10%
Rated voltage	25Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15.0%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

1 of 1



<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



<sup>2.</sup> This datasheet has only typical specifications because there is no space for detailed specifications.