


LLL216R71C104MA01#

" # " indicates a package specification code.

Available   Complies with RoHS 

< List of part numbers with package codes >
 LLL216R71C104MA01L , LLL216R71C104MA01K , LLL216R71C104MA01B

Shape



L size	1.25 ± 0.1mm
W size	2.0 ± 0.1mm
T size	0.6 ± 0.1mm
External terminal width e	± 0.1mm
Distance between external terminals g (Min.)	0.35mm
Size code in mm(inch)	1220 (0508)

References

Packaging	Specifications	Minimum quantity
L	Embossed tape (180mm)	4000
K	Embossed tape (330mm)	10000
B	Packing in bulk	1000

Mass (typ.)	
1 piece	7mg
Reel (180mm)	140g


Specifications

Capacitance	0.10µF ± 20%
Rated voltage	16Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125


Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.


▪ Frequency characteristics (ESR, Impedance)




▪ S parameter (Smith chart S11)



▪ DC bias characteristics



▪ AC voltage characteristics



▪ Capacitance - temperature characteristics

