

Search Engine > Catalog: TZ03Z070F169B00

Investor Relations

Capacitors > Ceramic Trimmer Capacitors

Specification

Global Part Number	TZ03Z070F169B00	
Previous Part Number	TZ03Z070FR169	
Cmin. (max.)	2.0pF	
Cmax.	7.0pF +50/-0%	
TC	NP0±200ppm/°C	
Q	500min. at 1MHz, Cmax.	
Rated Voltage	100Vdc	
Withstanding Voltage	220Vdc	
Insulation Resistance (min.)	10000M ohm	
Torque	2.0 to 15.0mNm	
Operating Temperature Range	-25 to +85°C	
Stator/Case Color	Blue	
Adjustment Direction	Тор	
Soldering Method	Flow	
Height	4.8mm ±0.5	
Weight	0.4g	

Minimum Quantity

180mm Paper Tape	
180mm Plastic Tape	
330mm Paper Tape	
330mm Plastic Tape	
Bulk Case	
Bulk(Bag)	1000
Ammo Pack	
320Reel	
Magazine	
Box	

Details



Part Numbering



Appearance



Dimensions



Features_and_Applications



Temp._Coeff._Characteristics



Frequency_Characteristics



Construction



Mounting_Holes



Notice_(Storage_and_operating_condition)



Temperature_Profile(Flow)



Notice_(Soldering_and_mounting)



Notice_(Handling)



Notice_(Other)

Product specifications in this catalog are as of May 2005, and are subject to change or obsolescence without notice.

Please approve our product specifications or transact the approval sheet before ordering. Please read rating and !Cautions first.

All products and company names herein are trademarks or registered trademarks of their respective owners.

|TOP|

All Rights Reserved, Copyright (c)

Murata Manufacturing Co., Ltd. 2005