

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

Technical Data ZC series



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series



Patr No.	Voltaeg / Cap.	Size (mm)	Page
EEHZC1E220R	25 V 22 μ F	Φ 5 x 5.8	... ZC- 1
EEHZC1E330R	25 V 33 μ F	Φ 5 x 5.8	... ZC- 2
EEHZC1E470P	25 V 47 μ F	Φ 6.3 x 5.8	... ZC- 3
EEHZC1E560P	25 V 56 μ F	Φ 6.3 x 5.8	... ZC- 4
EEHZC1E680XP	25 V 68 μ F	Φ 6.3 x 7.7	... ZC- 5
EEHZC1E101XP	25 V 100 μ F	Φ 6.3 x 7.7	... ZC- 6
EEHZC1E151P	25 V 150 μ F	Φ 8 x 10.2	... ZC- 7
EEHZC1E221P	25 V 220 μ F	Φ 8 x 10.2	... ZC- 8
EEHZC1E331P	25 V 330 μ F	Φ 10 x 10.2	... ZC- 9
EEHZC1V100R	35 V 10 μ F	Φ 5 x 5.8	... ZC- 10
EEHZC1V220R	35 V 22 μ F	Φ 5 x 5.8	... ZC- 11
EEHZC1V330P	35 V 33 μ F	Φ 6.3 x 5.8	... ZC- 12
EEHZC1V470P	35 V 47 μ F	Φ 6.3 x 5.8	... ZC- 13
EEHZC1V680XP	35 V 68 μ F	Φ 6.3 x 7.7	... ZC- 14
EEHZC1V101P	35 V 100 μ F	Φ 8 x 10.2	... ZC- 15
EEHZC1V151P	35 V 150 μ F	Φ 8 x 10.2	... ZC- 16
EEHZC1V221P	35 V 220 μ F	Φ 10 x 10.2	... ZC- 17
EEHZC1V271P	35 V 270 μ F	Φ 10 x 10.2	... ZC- 18
EEHZC1H100R	50 V 10 μ F	Φ 5 x 5.8	... ZC- 19
EEHZC1H220P	50 V 22 μ F	Φ 6.3 x 5.8	... ZC- 20
EEHZC1H330XP	50 V 33 μ F	Φ 6.3 x 7.7	... ZC- 21
EEHZC1H470P	50 V 47 μ F	Φ 8 x 10.2	... ZC- 22
EEHZC1H680P	50 V 68 μ F	Φ 8 x 10.2	... ZC- 23
EEHZC1H101P	50 V 100 μ F	Φ 10 x 10.2	... ZC- 24
EEHZC1H121P	50 V 120 μ F	Φ 10 x 10.2	... ZC- 25
EEHZC1J100P	63 V 10 μ F	Φ 6.3 x 5.8	... ZC- 26
EEHZC1J220XP	63 V 22 μ F	Φ 6.3 x 7.7	... ZC- 27
EEHZC1J330P	63 V 33 μ F	Φ 8 x 10.2	... ZC- 28
EEHZC1J470P	63 V 47 μ F	Φ 8 x 10.2	... ZC- 29
EEHZC1J560P	63 V 56 μ F	Φ 10 x 10.2	... ZC- 30
EEHZC1J680P	63 V 68 μ F	Φ 10 x 10.2	... ZC- 31
EEHZC1J820P	63 V 82 μ F	Φ 10 x 10.2	... ZC- 32
EEHZC1K220P	80 V 22 μ F	Φ 8 x 10.2	... ZC- 33
EEHZC1K330P	80 V 33 μ F	Φ 10 x 10.2	... ZC- 34
EEHZC1K470P	80 V 47 μ F	Φ 10 x 10.2	... ZC- 35

Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E220R

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	22 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.14 max. (at 120 Hz)
Leakage Current	5.5 μA max. (at R.V., After 2 min)
ESR	80 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	550 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: C (Unit: mm)

ΦD	5.0 ±0.5
L	5.8 ±0.3
A, B	5.3 ±0.2
H	6.5 max.
I	2.2
W	0.65 ±0.10
P	1.5
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E330R

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	33 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.14 max. (at 120 Hz)
Leakage Current	8.2 μA max. (at R.V., After 2 min)
ESR	80 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	550 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: C (Unit: mm)

ΦD	5.0 ±0.5
L	5.8 ±0.3
A, B	5.3 ±0.2
H	6.5 max.
I	2.2
W	0.65 ±0.10
P	1.5
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E470P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	47 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.14 max. (at 120 Hz)
Leakage Current	11.7 μA max. (at R.V., After 2 min)
ESR	50 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	900 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D (Unit: mm)

ΦD	6.3 ±0.5
L	5.8 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E560P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	56 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.14 max. (at 120 Hz)
Leakage Current	14.0 μA max. (at R.V., After 2 min)
ESR	50 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	900 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D (Unit: mm)

ΦD	6.3 ±0.5
L	5.8 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E680XP

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	68 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.14 max. (at 120 Hz)
Leakage Current	17.0 μA max. (at R.V., After 2 min)
ESR	30 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1400 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D8 (Unit: mm)

ΦD	6.3 ±0.5
L	7.7 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E101XP

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	100 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.14 max. (at 120 Hz)
Leakage Current	25.0 μA max. (at R.V., After 2 min)
ESR	30 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1400 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D8 (Unit: mm)

ΦD	6.3 ±0.5
L	7.7 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E151P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	150 μ F (at 120 Hz)
Capacitance Tolerance	\pm 20 %

$\tan \delta$	0.14 max. (at 120 Hz)
Leakage Current	37.5 μ A max. (at R.V., After 2 min)
ESR	27 m Ω max. (at 100 kHz, 20 °C)
Ripple Current	1600 mArms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: F (Unit: mm)

Φ D	8.0 \pm 0.5
L	10.2 \pm 0.3
A, B	8.3 \pm 0.2
H	10.0 max.
I	3.4
W	0.90 \pm 0.20
P	3.1
K	0.70 \pm 0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, $\tan \delta$ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, $\tan \delta$, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E221P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	220 μ F (at 120 Hz)
Capacitance Tolerance	\pm 20 %

$\tan \delta$	0.14 max. (at 120 Hz)
Leakage Current	55.0 μ A max. (at R.V., After 2 min)
ESR	27 m Ω max. (at 100 kHz, 20 °C)
Ripple Current	1600 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: F (Unit: mm)

Φ D	8.0 \pm 0.5
L	10.2 \pm 0.3
A, B	8.3 \pm 0.2
H	10.0 max.
I	3.4
W	0.90 \pm 0.20
P	3.1
K	0.70 \pm 0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, $\tan \delta$ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, $\tan \delta$, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1E331P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	25 V
Nominal Capacitance	330 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.14 max. (at 120 Hz)
Leakage Current	82.5 μA max. (at R.V., After 2 min)
ESR	20 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	2000 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ΦD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V100R

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	10 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	3.5 μA max. (at R.V., After 2 min)
ESR	100 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	550 mArms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





() : Reference size

Size Code: C (Unit: mm)

ΦD	5.0 ±0.5
L	5.8 ±0.3
A, B	5.3 ±0.2
H	6.5 max.
I	2.2
W	0.65 ±0.10
P	1.5
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V220R

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	22 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	7.7 μA max. (at R.V., After 2 min)
ESR	100 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	550 mArms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





() : Reference size

Size Code: C (Unit: mm)

ΦD	5.0 ±0.5
L	5.8 ±0.3
A, B	5.3 ±0.2
H	6.5 max.
I	2.2
W	0.65 ±0.10
P	1.5
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V330P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	33 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	11.5 μA max. (at R.V., After 2 min)
ESR	60 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	900 mA _{rms} max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D (Unit: mm)

ΦD	6.3 ±0.5
L	5.8 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 V_{rms} (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 V_{rms} (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V470P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	47 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	16.4 μA max. (at R.V., After 2 min)
ESR	60 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	900 mArms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D (Unit: mm)

ΦD	6.3 ±0.5
L	5.8 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V680XP

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	68 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	23.8 μA max. (at R.V., After 2 min)
ESR	35 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1400 mArms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





() : Reference size

Size Code: D8 (Unit: mm)

ΦD	6.3 ±0.5
L	7.7 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V101P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	100 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	35.0 μA max. (at R.V., After 2 min)
ESR	27 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1600 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





() : Reference size

Size Code: F (Unit: mm)

ΦD	8.0 ±0.5
L	10.2 ±0.3
A, B	8.3 ±0.2
H	10.0 max.
I	3.4
W	0.90 ±0.20
P	3.1
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V151P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	150 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	52.5 μA max. (at R.V., After 2 min)
ESR	27 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1600 mArms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





() : Reference size

Size Code: F (Unit: mm)

ΦD	8.0 ±0.5
L	10.2 ±0.3
A, B	8.3 ±0.2
H	10.0 max.
I	3.4
W	0.90 ±0.20
P	3.1
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V221P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	220 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	77.0 μA max. (at R.V., After 2 min)
ESR	20 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	2000 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ΦD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1V271P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	35 V
Nominal Capacitance	270 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.12 max. (at 120 Hz)
Leakage Current	94.5 μA max. (at R.V., After 2 min)
ESR	20 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	2000 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ΦD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1H100R

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	50 V
Nominal Capacitance	10 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.10 max. (at 120 Hz)
Leakage Current	5.0 μA max. (at R.V., After 2 min)
ESR	120 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	500 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: C (Unit: mm)

ΦD	5.0 ±0.5
L	5.8 ±0.3
A, B	5.3 ±0.2
H	6.5 max.
I	2.2
W	0.65 ±0.10
P	1.5
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1H220P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	50 V
Nominal Capacitance	22 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.10 max. (at 120 Hz)
Leakage Current	11.0 μA max. (at R.V., After 2 min)
ESR	80 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	750 mArms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D (Unit: mm)

ϕD	6.3 ±0.5
L	5.8 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1H330XP

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	50 V
Nominal Capacitance	33 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.10 max. (at 120 Hz)
Leakage Current	16.5 μA max. (at R.V., After 2 min)
ESR	40 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1100 mArms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D8 (Unit: mm)

ΦD	6.3 ±0.5
L	7.7 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1H470P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	50 V
Nominal Capacitance	47 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.10 max. (at 120 Hz)
Leakage Current	23.5 μA max. (at R.V., After 2 min)
ESR	30 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1250 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: F (Unit: mm)

ΦD	8.0 ±0.5
L	10.2 ±0.3
A, B	8.3 ±0.2
H	10.0 max.
I	3.4
W	0.90 ±0.20
P	3.1
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1H680P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	50 V
Nominal Capacitance	68 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.10 max. (at 120 Hz)
Leakage Current	34.0 μA max. (at R.V., After 2 min)
ESR	30 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1250 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





() : Reference size

Size Code: F (Unit: mm)

ΦD	8.0 ±0.5
L	10.2 ±0.3
A, B	8.3 ±0.2
H	10.0 max.
I	3.4
W	0.90 ±0.20
P	3.1
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1H101P

Endurance: 125 °C, 4000 h



Category Temperature Range	-55 °C to 125 °C
Rated Voltage	50 V
Nominal Capacitance	100 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.10 max. (at 120 Hz)
Leakage Current	50.0 μA max. (at R.V., After 2 min)
ESR	28 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1600 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ϕD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1H121P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	50 V
Nominal Capacitance	120 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.10 max. (at 120 Hz)
Leakage Current	60.0 μA max. (at R.V., After 2 min)
ESR	28 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1600 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ΦD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1J100P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	63 V
Nominal Capacitance	10 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	6.3 μA max. (at R.V., After 2 min)
ESR	120 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	700 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D (Unit: mm)

ΦD	6.3 ±0.5
L	5.8 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1J220XP

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	63 V
Nominal Capacitance	22 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	13.8 μA max. (at R.V., After 2 min)
ESR	80 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	900 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: D8 (Unit: mm)

ΦD	6.3 ±0.5
L	7.7 ±0.3
A, B	6.6 ±0.2
H	7.8 max.
I	2.6
W	0.65 ±0.10
P	1.8
K	0.35 +0.15/-0.20



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1J330P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	63 V
Nominal Capacitance	33 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	20.7 μA max. (at R.V., After 2 min)
ESR	40 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1100 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: F (Unit: mm)

ΦD	8.0 ±0.5
L	10.2 ±0.3
A, B	8.3 ±0.2
H	10.0 max.
I	3.4
W	0.90 ±0.20
P	3.1
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1J470P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	63 V
Nominal Capacitance	47 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	29.6 μA max. (at R.V., After 2 min)
ESR	40 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1100 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: F (Unit: mm)

ϕD	8.0 ±0.5
L	10.2 ±0.3
A, B	8.3 ±0.2
H	10.0 max.
I	3.4
W	0.90 ±0.20
P	3.1
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1J560P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	63 V
Nominal Capacitance	56 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	35.2 μA max. (at R.V., After 2 min)
ESR	30 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1400 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ϕD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1J680P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	63 V
Nominal Capacitance	68 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	42.8 μA max. (at R.V., After 2 min)
ESR	30 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1400 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ΦD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1J820P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	63 V
Nominal Capacitance	82 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	51.6 μA max. (at R.V., After 2 min)
ESR	30 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1400 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ΦD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1K220P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	80 V
Nominal Capacitance	22 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	17.6 μA max. (at R.V., After 2 min)
ESR	45 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1050 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: F (Unit: mm)

ΦD	8.0 ±0.5
L	10.2 ±0.3
A, B	8.3 ±0.2
H	10.0 max.
I	3.4
W	0.90 ±0.20
P	3.1
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1K330P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	80 V
Nominal Capacitance	33 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	26.4 μA max. (at R.V., After 2 min)
ESR	36 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1360 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ϕD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



Data Sheet

Conductive Polymer Hybrid Aluminum Electrolytic Capacitor

SMD type ZC series


Part Number : EEHZC1K470P

Endurance: 125 °C, 4000 h


Category Temperature Range	-55 °C to 125 °C
Rated Voltage	80 V
Nominal Capacitance	47 μF (at 120 Hz)
Capacitance Tolerance	±20 %

tan δ	0.08 max. (at 120 Hz)
Leakage Current	37.6 μA max. (at R.V., After 2 min)
ESR	36 mΩ max. (at 100 kHz, 20 °C)
Ripple Current	1360 mA rms max. (at 100 kHz, 125 °C)

Marking



Dimensions in mm (not to scale)





Size Code: G (Unit: mm)

ΦD	10.0 ±0.5
L	10.2 ±0.3
A, B	10.3 ±0.2
H	12.0 max.
I	3.5
W	0.90 ±0.20
P	4.6
K	0.70 ±0.2



Frequency vs. Impedance, ESR, ESL, Capacitance, tanδ Characteristics

Osc. Level: 0.5 Vrms (at no load)



Temperature vs. Capacitance, tanδ, ESR Characteristics

Osc. Level: 0.5 Vrms (at no load)



**Conductive Polymer Hybrid
Aluminum Electrolytic Capacitors**

Technical Data ZC series

The first edition : July 1st 2013

The revised edition : April 21, 2020

Issued by Industrial Solutions Company Panasonic Co., Ltd.

Device Solutions Business Division

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.