

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFBS100445 Pro
 - Part Drawings
 - PDFBraided Bond..
 - Specification Sheets
 - PDFStructuredGr ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'BS101245U'

Your search criteria matched only one product, shown below

BS101245U



- Used to electrically bond enclosure doors, motors, and machine frames in the construction of control panels or machine structures
- Flat ferrule end design helps to reduce the effects of EMI (Electromagnetic Interference)
- Available with internationally recognized green and yellow insulation for grounding application
- Made of high conductivity copper and tin-plated to inhibit corrosion
- Seamless ferrule ends provide mechanical strength for improved reliability

Part Number	BS101245U
RoHS Compliancy Status	Compliant
Part Description	Braided Bonding Strap, onehole, non-insulated, 12.00" length x 1.06" width (304.8mm x 27.0mm).
Depth (In.)	11.00
Depth (mm)	279.4
Height (In.)	12.00
Height (mm)	304.8
Length (In.)	12.00
Length (mm)	304.8
Width (In.)	1.06
Width (mm)	27.0
Copper Conductor Size	#4 AWG
Stud Hole Size (In.)	3/8
Ferrule Length (In.)	1.00
Ferrule Length (mm)	25.4
Pricing Description	Braided Bonding Strap, OneHole, NonInsulated, 12" x 1.06" (304.8mm x 27.0mm)
Stud Hole Size (mm)	M10
Thickness (In.)	0.13
Thickness (mm)	3.3
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.