


Search Results

- Evaluate
  - FAQ's
- Design a Solution
  - Catalog Cut Sheet
  - PDFDMV1-63P-LY
  - Part Drawings
  - PDFMetric Piggy..
- How to Buy
  - Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips


 Text Search: 'DMV1-63P-LY'

Your search criteria matched only one product, shown below

**DMV1-63P-LY**



- Combination of female disconnect and male tab allows versatility in points of connection
- Multiple connection points allow additional circuits to be added to existing equipment without expensive rework
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Maximum insulation temperature 194°F (90°C)
- Rated up to 600 V

Part Number	DMV1-63P-LY
RoHS Compliant Status	Compliant
Note	DMV1-63P-LY replaces DMV1-63P-L
Part Description	Metric Piggyback Disconnect, vinyl barrel insulated, 0.5- 1.0mm <sup>2</sup> wire range, 6.3 x .8mm tab size
Product Type	Disconnects - Metric
Length (mm)	22.4
Width (mm)	7.4
CE Compliant	No
Insulation	Vinyl
Max. Ins. (mm)	3.30
Panduit Color Code	Red
Plating Type	Tinned
Pricing Description	Metric Piggyback Disconnect, vinyl barrel insulated, 0.5- 1.0mm <sup>2</sup> wire range, 6.3 x .8mm tab size
Tab Size (mm)	6.3 x 0.8
Temperature Rating	194 Degrees Fahrenheit (90 Degrees Celsius)
Tool	CT-1551
Wire Range (mm <sup>2</sup> )	0.5 – 1.0
Min. Order UOM	PC
Min. Order Qty.	50
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.